

SHOWA

# SHOWA 893

Black

Forged with fluoroelastomer rubber, SHOWA 893 provides superior resistance to highly corrosive acids and is designed for handling aliphatic and aromatic hydrocarbons, such as Benzene, Toulene, and Xylene.

## [ FEATURES

## [ BENEFITS

Protection against aromatics such as benzene, toluene, xylene.

Excellent barrier to most chlorinated solvents and aliphatic hydrocarbons.

## [ INDUSTRY



Chemical



Construction



Manufacturing

## [ IDEAL APPLICATIONS

- Chemical spray and treatment
- Coating preparation
- Laboratory, pharma & analysis
- Painting & spray workshops



## COATING

- Viton

## GRIP

- Smooth

## STANDARDS

Cat. II



SHOWA

# SHOWA 893

**Black**

 **PACKAGING**



**SIZES**

- S
- M
- L
- XL

**COLOUR**

- Black



## [ YOU MIGHT ALSO BE INTERESTED IN

SHOWA  
**892**



**MATERIAL**  
Unsupported  
**COATING**  
chemical  
resistant

SHOWA  
**890**



**MATERIAL**  
Unsupported  
**COATING**  
chemical  
resistant

## [ USER INSTRUCTIONS

Protection against mechanical risks, with electrostatic properties. Do not use where there are chemical, electrical, thermal or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. The performance levels apply to the coated surface only. Store in a dry place, away from the light. All clothing and shoes worn with the glove with electrostatic dissipation properties must also be designed taking the electrostatic risk into account.

## [ DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

**Get in touch**

SHOWA USA | 579 Edison Street - Menlo, GA 30731, USA

USA@SHOWAGroup.com

© SHOWA Group 2018 | All rights reserved