

Honeywell Burdick & Jackson High-Purity Solvents

When purchasing solvents for an analytical lab, a wide range of choices are available to both the scientist and the purchasing department. Choosing the correct grade can be a challenging and daunting task, but is a critical step to obtain the desired outcome cost effectively.

First and foremost, one has to consider the intended application of the solvent. Some lab applications may be fairly routine, high volume, and non-demanding, such as glassware cleaning, organic synthesis reactions, prep scale chromatography or well-characterized QC applications. Applications such as these normally require a lower quality, cost effective grade of solvent which will still guarantee acceptable results. Choosing a higher grade product for these types of routine applications may not be the most cost effective solution.

On the other hand, applications such as GC-MS, HPLC, UPLC and LC-MS require a specialized or highly purified grade of solvent that meets the stringent performance requirements of the trace analysis research. This will also ensure that users get the most sensitivity from the instrument, as well as prevent instrument downtime associated with cleaning due to using lower quality solvents that leave residuals in the instrument. Other benefits from using higher quality solvents include minimizing rework, greater precision and accuracy, enhanced instrument performance, increased reproducibility, decreased instrument consumables, and increased analyst efficiency. Even though the cost of these higher purity solvents can be slightly more than the lower grade products, this cost can be recovered through the benefits described above.

When selecting a grade of solvent, the technical experts from Honeywell Burdick & Jackson™ (B&J) recommend that the material be “functionally” tested within the application to ensure its suitability. As an example, if selecting a HPLC grade of Methanol, and the application is a HPLC gradient





analysis, it is an important factor to verify that the grade you select has both a HPLC gradient specification along with UV absorbance and fluorescence specifications. This will ensure that the grade is appropriate for the majority of these HPLC applications. This rule also applies when performing LC-MS analysis. Again, B&J experts recommend that users verify that the LC-MS solvents selected be functionally tested by LC-MS (typically ESI positive as well as ESI negative modes). It is also important that a LC-MS grade of solvent have very stringent metal specifications (ppb levels) to prevent the formation of adducts. If unsure as to where to find the solvent specifications, they can normally be found on the solvent label, certificate of analysis, or at most solvent manufactures' websites.

There are other specialized applications that require the solvents to have unique specifications. Some examples of these applications include RNA/DNA synthesis (which require solvents to be very dry, low residue, and have low amine content), some organic synthesis reactions (which require anhydrous solvents), environmental applications (which may require electron capture of flame ionization specifications) and the list goes on and on. The key point is that when doing these types of applications (or others not listed), it is extremely important to verify that solvents used for these applications have specifications that will guarantee that they are suitable for that particular application.

For a list of product grades by application, please refer to B&J's Application Guide by Product Line on the next page.

AMERICAS

Honeywell Corporate Headquarters

115 Tabor Road
Morris Plains, NJ 07950

Manufacturing Facility

1953 South Harvey Street
Muskegon, MI 49442

EUROPE

Honeywell Specialty Chemicals

Seelze GmbH
Manufacturing Facility
Wunstorferstrasse 40
30926 Seelze, Germany

ASIA/PACIFIC

Asia Pacific Headquarters

Honeywell (China) Co. Ltd.
430 Li Bing Road
Zhang Jiang Hi-Tech Park
Pudong New Area
Shanghai 201203

Honeywell Specialty Chemicals

New Pier Takeshiba, South
Tower Building
20th Floor, 1-16-1 Kaigan
Minato-ku, Tokyo, Japan
1050022

Burdick & Jackson™ is a trademark of Honeywell International Inc.

All statements and information provided herein are believed to be accurate and reliable, but are presented without guarantee, warranty or responsibility of any kind, express or implied. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement, and are not recommendations to infringe any patent. The user should not assume that all safety measures are indicated herein, or that other measures may not be required. User assumes all liability for use of the information and results obtained.



3304 RC I v2 | September 2018

© 2018 Honeywell International Inc. All rights reserved.

Honeywell