



Item # _____

Job _____

Built for Labs and Cleanrooms using the most stringent cleaning agents.

HD SUPER™

WORK CENTERS with 316 Stainless Steel Table Tops

- **316 Table Tops** can withstand corrosive attacks by sodium, calcium brines, hypochlorite solutions, phosphoric acids, sulfate and sulfuric acid.
- **Heavy-Duty:** HD Super™ Work Centers are designed and built for heavy-duty applications. The work surface is made of seamless, 16-gauge stainless steel with an 11-gauge support structure that virtually eliminates any "drumming".
- **Greater Rigidity:** Work Centers features 1 5/8" diameter HD Super™ posts and the tapered sleeves and corners of patented Super Erecta Shelf® construction. These two features assure a rigid, wobble-free table.
- **Easy to Assemble:** Units are shipped knocked down and can be put together in minutes without special tools. Bottom shelf of frame is adjustable in 2" (51mm) increments. The table top fits over plastic sleeves at the top of the posts.
- **Several Styles Available:** Versatile HD Super™ Work Centers come in 22 models, all with 316 stainless steel tops, but offering a choice of chrome-plated or stainless steel posts and either a shelf or a three-sided frame which can be placed at the desired level below the top. Additional shelves can be ordered from HD Super™ stock.
- **Stationary or Mobile:** Standard units are stationary with leveling foot on each post. Work Centers are also available fitted with 5" (127mm) polyurethane swivel casters, two with wheel brake.
- **Popular Sizes:** Work Centers come in 30" (760mm) width and lengths of 60", 72" and 96" (1525, 1825 and 2440mm). All models are 34" (860mm) high.



Work Center with Shelf. Deluxe Drawer shown sold separately.



Work Center with 3-Sided Tubular Frame



InterMetro Industries Corporation
North Washington Street
Wilkes-Barre, PA 18705
www.metro.com



Work Center with
“H” Frame

Dimensions

Standard Work Centers

30" (760mm) Wide

Cat. No.	Length (in.)	Post (mm) Material	Bottom Shelf Material (16 ga.)	Bottom 3-Sided Frame Material (16 ga.)	Bottom H-Frame Material (16 ga.)	Approx. Pkd. Wt. (lbs.)	(kg)	
WT305FS-316T	48	1219	SS	SS	—	157.03	71.23	
WT306FS-316T	60	1525	SS	SS	—	198.20	89.90	
WT307FS-316T	72	1825	SS	SS	—	235.20	106.68	
WT309FS-316T	96	2439	SS	SS	—	268.20	121.65	
WT305US-316T	48	1219	SS	—	SS	145.20	65.86	
WT306US-316T	60	1525	SS	—	SS	176.20	76.92	
WT307US-316T	72	1825	SS	—	SS	210.20	95.35	
WT309US-316T	96	2439	SS	—	SS	243.20	110.31	
WT306HS-316T	60	1525	SS	—	—	SS	175.20	79.47
WT307HS-316T	72	1825	SS	—	—	SS	211.20	95.80
WT309HS-316T	96	2439	SS	—	—	SS	244.20	110.77

Load Ratings: 60" long units-625 lbs. (283kg); 72" long units-750 lbs. (340 kg); 96" long units-1000 lbs. (454kg), equally distributed.

Load Ratings: 60" long units-625 lbs. (283kg); 72" long units-750 lbs. (340 kg); 96" long units-1000 lbs. (454kg), equally distributed.

Accessories

Economy Drawer

Cat. No.	Overall Dimensions Width/Length/Height		Dimensions Inside Bottom		Approx. Pkd. Wt.		
	(in.)	(mm)	(in.)	(mm)	(lbs.)	(kg)	
WTD21C	14½	28x5¾	362x711	10x16	254x406	6.8	3.1



Deluxe Drawer

Cat. No.	Overall Dimensions Width/Length/Height		Dimensions Inside Bottom		Approx. Pkd. Wt.		
	(in.)	(mm)	(in.)	(mm)	(lbs.)	(kg)	
WTD51S	24	25¾x7½	610x654	20x20	508x508	31	13.9



HD SUPER™ 316 Stainless Steel Top WORK CENTERS



Dimensions

Mobile Work Centers

30" (760mm) Wide

Cat. No.	Length		Post	Bottom	Bottom	Bottom	Approx.	
	(in.)	(mm)	(mm)	Shelf	3-Sided	H-Frame		
			Material	Material	Frame	Material	(lbs.)	(kg)
				(16 ga.)	Material	(16 ga.)		
MWT305FS-316T	48	1219	SS	SS	—	—	171.53	77.80
MWT306FS-316T	60	1525	SS	SS	—	—	212.70	96.48
MWT307FS-316T	72	1825	SS	SS	—	—	249.70	113.26
MWT309FS-316T	96	2439	SS	SS	—	—	282.70	128.23
MWT305US-316T	48	1219	SS	SS	—	—	159.70	72.44
MWT306US-316T	60	1525	SS	—	SS	—	190.70	86.50
MWT307US-316T	72	1825	SS	—	SS	—	224.70	101.92
MWT309US-316T	96	2439	SS	—	SS	—	257.70	116.89
MWT306HS-316T	60	1525	SS	—	—	SS	178.50	80.96
MWT307HS-316T	72	1825	SS	—	—	SS	211.70	96.03
MWT309HS-316T	96	2439	SS	—	—	SS	244.70	110.99

Load Ratings: 60" long units-625 lbs. (283kg); 72" long units-750 lbs. (340 kg); 96" long units-1000 lbs. (454kg), equally distributed.

Specifications

- **Top:** Seamless 16-gauge 316 stainless steel, with 11-gauge channel support, nickel/chrome-plated after fabrication.
- **Bottom Shelf:** 16-gauge galvanized for 304 stainless steel. 14-gauge available on special order. 30" x 60" (760 x 1525mm) work centers have 24" x 54" (610 x 1370mm) bottom shelves; 30" x 72" (760 x 1825mm) and 30" x 96" (760 x 2440mm) work centers have 24" x 60" (610 x 1525mm) bottom shelves.
- **Bottom Frame:** Three-sided tubular frame available in 16-gauge stainless steel. 30" x 60" (760 x 1525mm) work centers have 24" x 54" (610 x 1370mm) bottom frames; 30" x 72" (760 x 1825mm) and 30" x 96" (760 x 2440mm) work centers have 24" x 60" (610 x 1525mm) bottom frames.
- **Posts:** Steel posts have an outside diameter of 1.58" (38mm), with rolled grooves in 2" (51mm) increments along entire height.

Manufactured by:



InterMetro Industries Corporation

North Washington Street, Wilkes-Barre, PA 18705

Phone: 570-825-2741 • Fax: 570-825-2852

For Product Information Call: 1-800-433-2232

Visit Our Web Site: www.metro.com

LO-242
Rev. 03/20
Printed in U.S.A.

Information and specifications are subject to change without notice. Please confirm at time of order.