


## Corning® Microcarriers



hMSC on Corning Synthemax II microcarriers



100 g and 500 g bottles with aseptic transfer caps

Corning Microcarriers simplify the scale-up process. The beads arrive sterile, ready-to-use, and are available with surface treatments to enhance cell attachment and maximize cell yield and viability. Closed systems packaging is also available for use with bioreactors.

### Features

- ▶ USP Class VI polystyrene material provides a consistent platform
- ▶ Available untreated or with three different surface treatments
- ▶ Sterility Assurance Level (SAL) of 10<sup>-6</sup>
- ▶ Nonpyrogenic
- ▶ Large sizes available with closed systems packaging

### Microcarrier Surfaces

Surface	Properties	Bead Size (µm)	Approx. Density (cm <sup>3</sup> /g)	Surface Area (cm <sup>2</sup> /g)	10 g Vial	100 g Bottle	500 g Bottle	Closed System
Enhanced Attachment Corning CellBIND®	Incorporates more oxygen into the cell culture surface, rendering it more hydrophilic and increasing cell attachment. No special handling or storage required. Nonbiological.	125 - 212	1.026	360	■	■	■	■
Low Concentration Corning Synthemax™ II	Synthetic surface for stem cell expansion. Recommended for MSCs.	125 - 212	1.026	360	■	■	■	■
Collagen-coated	Extracellular matrix protein enhances attachment and performance of some cell types.	125 - 212	1.026	360	■			
Untreated		125 - 212	1.026	360	■	■	■	■

### Closed Systems Packaging

Corning microcarriers with Corning CellBIND, low concentration Synthemax II, and untreated surfaces are available in 100 g and 500 g bottles that can be fitted with Corning aseptic transfer caps to prevent adventitious contamination during bioreactor loading. The transfer caps are available with either a male Luer lock quick connector or an MPC quick connect. Microcarriers and aseptic transfer caps are sold separately.

## Ordering Information

### Corning® Microcarriers



Corning Microcarriers,  
10 g vials

VWR Cat. No.	Corning Cat. No.	Description	Size	Qty/Cs
30617-554	3779	Corning CellBIND® surface microcarriers	10 g	1
10002-712	4620	Corning CellBIND surface microcarriers	100 g	1
10002-704	4621	Corning CellBIND surface microcarriers	500 g	1
30617-552	3781	Corning low concentration Synthemax™ II microcarriers	10 g	1
10002-706	4622	Corning low concentration Synthemax II microcarriers	100 g	1
10002-708	4623	Corning low concentration Synthemax II microcarriers	500 g	1
89499-408	3786	Corning Collagen-coated microcarriers	10 g	1
89499-404	3772	Corning untreated microcarriers	10 g	1
10002-710	4624	Corning untreated microcarriers	100 g	1
10002-714	4625	Corning untreated microcarriers	500 g	1

### Aseptic Transfer Caps for 100 g and 500 g Sizes

VWR Cat. No.	Corning Cat. No.	Description	Tubing	Tubing Length with Connector	Tubing Connection	Qty/Cs
10002-716	4626	Aseptic transfer cap for 100 g bottles	Chemically resistant, heat sealable flexible tubing, 1/8" ID, 1/4" OD	30" (76.2 cm)	MLL	1
10002-718	4627	Aseptic transfer cap for 100 g bottles	Chemically resistant, heat sealable flexible tubing, 1/4" ID, 3/8" OD	30" (76.2 cm)	MPC	1
10002-720	4628	Aseptic transfer cap for 500 g bottles	Chemically resistant, heat sealable flexible tubing, 1/8" ID, 1/4" OD	30" (76.2 cm)	MLL	1
10002-722	4629	Aseptic transfer cap for 500 g bottles	Chemically resistant, heat sealable flexible tubing, 1/4" ID, 3/8" OD	30" (76.2 cm)	MPC	1

MLL: Male Luer lock; MPC: Medical plastic coupler

**Warranty/Disclaimer:** Unless otherwise specified, these products are US class I medical devices for cell and tissue culture. Corning does not make or support any further claim for these products nor does it conduct any further testing to support any other intended use for the product indicated above. Should you decide that you want to use the product for any intended use other than that made by Corning then you accept that Corning does not make or support that claim and that you as the user are responsible for any testing, validation, and/or regulatory submissions that may be required to support the safety and efficacy of your intended application.

# CORNING

For additional product or technical information, visit [vwr.com/corning](http://vwr.com/corning), call 1.800.932.5000, or contact your VWR representative.

**avantor™**  
delivered by **VWR™**

VWR.COM

Prices, product, and/or services details are current when published and subject to change without notice. | Certain products or services may be limited by federal, state, provincial, or local regulations. | VWR, part of Avantor, makes no claims or warranties concerning sustainable/green products. Any claims concerning sustainable/green products are the sole claims of the manufacturer and not those of VWR International, LLC and/or Avantor, Inc. or affiliates. All prices are in US dollars unless otherwise noted. Offers valid in US and Canada unless otherwise noted, void where prohibited by law or company policy, while supplies last. | Trademarks are owned by Avantor, Inc. or its affiliates, unless otherwise noted. | Visit [vwr.com](http://vwr.com) to view our privacy policy, trademark owners, and additional disclaimers. © 2021 Avantor, Inc. All rights reserved.