Product Name:	NSWDR121WWG/0
Description:	Corepoint Scientific™ White Diamond Series Laboratory and Medical Refrigerator 12 Cu. Ft. Capacity One swing glass door, self-closing (energy efficient, double pane vacuum insulated), right hinged Microprocessor temperature controller Touch Screen Digital Temperature Display with user friendly interface Alarm Module with battery back-up to support temperature monitoring and alarms Password-protected control panel C°/F° switchable .1° Resolution Adjustable operating temperature: 1°C to 10°C Active temperature scale bar display Resettable 1-point min/max history Digital 24-hour temperature chart Temperature data logging USB port for data transfer and software updates Real-time operational display clock 4-20mA output Adjustable alarm volume Audible and visual high and low temperature alarms 2 probes; 1 in air and 1 in sample bottle Sensor error alarm Power failure alarm Door ajar alarm Low battery alarm Alarm validation (audible, visual, and remote alarm) Alarm mute with ring back Remote alarm contacts Customizable alarm time delay settings Five adjustable shelves (adjustable in ½" increments) Forced draft air circulation Keyed door lock Magnetic door gasket for positive seal Heavy duty door handle LED interior lights are safety shielded and switch controlled
	Alarm validation (audible, visual, and remote alarm) Alarm mute with ring back Remote alarm contacts Customizable alarm time delay settings Five adjustable shelves (adjustable in ½" increments) Forced draft air circulation Keyed door lock Magnetic door gasket for positive seal
	LED interior lights are safety shielded and switch controlled Swivel casters (3 ½")  Probe access port (3/8")  White powder-coated steel exterior and interior  Hydrocarbon, natural refrigerant (R290)  Easily cleaned smooth interior  Three-year parts and labor warranty, plus an additional two year compressor parts warranty  Exterior dimensions: 25" W x 29 ¾" D x 66 1/2" H with casters; 62 ¼" H without casters  Cycle defrost  115V, 60 Hz, 3 Amps, 1/5 HP  ETL listed  Shipping weight: 258 lbs.