

Material Safety Data Sheet

Bradford Kit



Section 1. Product and Company Identification

Product name : Bradford Kit
Product code : 2740
Synonym : None.
Material uses : Other non-specified industry: Analytical reagent.
Manufacturer : EMD Chemicals Inc.
P.O. Box 70
480 Democrat Road
Gibbstown, NJ 08027
856-423-6300 Technical Service
Monday - Friday: 8:00 - 5:00 PM
Validation date : **11/17/2008.**
Print date : 11/17/2008.
In case of emergency : 800-424-9300 CHEMTREC (USA)
613-996-6666 CANUTEC (Canada)
24 Hours/Day: 7 Days/Week

Section 2. Hazards Identification

Physical state : Liquid.
OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Emergency overview : DANGER!
CAUSES RESPIRATORY TRACT, EYE AND SKIN BURNS.
HARMFUL IF INHALED OR SWALLOWED.
CONTAINS MATERIAL WHICH CAUSES DAMAGE TO THE FOLLOWING ORGANS:
BLOOD, REPRODUCTIVE SYSTEM, LIVER, RESPIRATORY TRACT, SKIN,
CENTRAL NERVOUS SYSTEM, EYE, LENS OR CORNEA.
Do not ingest. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist.
Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.
Routes of entry : Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

Eyes : Corrosive to eyes.
Skin : Corrosive to the skin.
Inhalation : Toxic by inhalation. Corrosive to the respiratory system.
Ingestion : Toxic if swallowed. May cause burns to mouth, throat and stomach.
Carcinogenic effects : No known significant effects or critical hazards.
Mutagenic effects : No known significant effects or critical hazards.
**Teratogenicity /
Reproductive toxicity** : No known significant effects or critical hazards.

Medical conditions aggravated by over-exposure : Repeated skin exposure can produce local skin destruction or dermatitis. Repeated or prolonged exposure to the substance can produce lung damage. Repeated or prolonged contact with spray or mist may produce chronic eye irritation and severe skin irritation. Repeated or prolonged exposure to the substance can produce target organs damage.

See toxicological information (section 11)

Continued on Next Page

Section 3. Composition/Information on Ingredients

United States

<u>Name</u>	<u>CAS number</u>	<u>% by Weight</u>
Water	7732-18-5	80 - 100
Phosphoric Acid	7664-38-2	7 - 13
Ethanol	64-17-5	3 - 7
Coomassie Blue (TM) G-250	6104-58-1	0 - 1

Section 4. First Aid Measures

- Eye contact** : Get medical attention immediately. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Chemical burns must be treated promptly by a physician.
- Skin contact** : Get medical attention immediately. Flush contaminated skin with plenty of water. Continue to rinse for at least 10 minutes. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing or wear gloves. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Inhalation** : Get medical attention immediately. Move exposed person to fresh air. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Ingestion** : Get medical attention immediately. Wash out mouth with water. Remove dentures if any. Move exposed person to fresh air. Keep person warm and at rest. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing or wear gloves.

Section 5. Fire Fighting Measures

- Flammability of the product** : No specific hazard.
- Products of combustion** : These products are carbon oxides (CO, CO₂), phosphates.
- Extinguishing media**
- Suitable** : Use an extinguishing agent suitable for the surrounding fire.
- Not suitable** : None known.
- Special exposure hazards** : Not available.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental Release Measures

- Personal precautions** : Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment.
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- Methods for cleaning up** : If emergency personnel are unavailable, contain spilled material. For small spills, add absorbent (soil may be used in the absence of other suitable materials), scoop up material and place in a sealable, liquid-proof container for disposal. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.

Section 7. Handling and Storage

- Handling** : Do not ingest. Do not get in eyes or on skin or clothing. Keep container closed. Use only with adequate ventilation. Do not breathe vapor or mist. Wash thoroughly after handling.
- Storage** : Keep container tightly closed. Keep container in a cool, well-ventilated area.

Section 8. Exposure Controls/Personal Protection

Product name

Exposure limits

United States

Phosphoric Acid

ACGIH TLV (United States, 1/2006).

STEL: 3 mg/m³ 15 minute/minutes. Form: All forms

TWA: 1 mg/m³ 8 hour/hours. Form: All forms

NIOSH REL (United States, 12/2001).

STEL: 3 mg/m³ 15 minute/minutes. Form: All forms

TWA: 1 mg/m³ 10 hour/hours. Form: All forms

OSHA PEL (United States, 8/1997).

TWA: 1 mg/m³ 8 hour/hours. Form: All forms

OSHA PEL 1989 (United States, 3/1989).

STEL: 3 mg/m³ 15 minute/minutes. Form: All forms

TWA: 1 mg/m³ 8 hour/hours. Form: All forms

Ethanol

ACGIH TLV (United States, 1/2005). Notes: 1996 Adoption Refers to Appendix A -- Carcinogens.

TWA: 1880 mg/m³ 8 hour/hours. Form: All forms

TWA: 1000 ppm 8 hour/hours. Form: All forms

NIOSH REL (United States, 12/2001).

TWA: 1900 mg/m³ 10 hour/hours. Form: All forms

TWA: 1000 ppm 10 hour/hours. Form: All forms

OSHA PEL (United States, 8/1997).

TWA: 1900 mg/m³ 8 hour/hours. Form: All forms

TWA: 1000 ppm 8 hour/hours. Form: All forms

OSHA PEL 1989 (United States, 3/1989).

TWA: 1900 mg/m³ 8 hour/hours. Form: All forms

TWA: 1000 ppm 8 hour/hours. Form: All forms

Consult local authorities for acceptable exposure limits.

- Engineering measures** : Use only with adequate ventilation. If user operations generate dust, fumes, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Personal protection

- Eyes** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.
Recommended: splash goggles , face shield

Section 8. Exposure Controls/Personal Protection

- Skin** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Body: Recommended: safety apron
- Respiratory** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Hands** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Section 9. Physical and Chemical Properties

- Physical state** : Liquid.
- Flash point** : The lowest known value is Closed cup: 12.85°C (55.1°F). (Ethanol)
- Auto-ignition temperature** : The lowest known value is 398.85°C (749.9°F) (Ethanol).
- Boiling/condensation point** : The lowest known value is 78.35°C (173°F) (Ethanol). Weighted average: 98.77°C (209.8°F)
- Melting/freezing point** : May start to solidify at -0.1°C (31.8°F) based on data for: Water. Weighted average: -6.09°C (21°F)
- Relative density** : Weighted average: 1.28 (Water = 1)
- Vapor density** : The highest known value is 1.6 (Air = 1) (Ethanol).
- Evaporation rate** : 1.7 (Ethanol) compared with Butyl acetate.

Section 10. Stability and Reactivity

- Stability and reactivity** : The product is stable.
- Incompatibility with various substances** : Reactive or incompatible with the following materials: metals and alkalis.
- Hazardous decomposition products** : carbon oxides (CO, CO₂) , nitrogen oxides (NO, NO₂ etc.) , sulfur oxides (SO₂, SO₃ etc.)
- Hazardous polymerization** : Will not occur.
- Conditions of reactivity** : Explosive in the presence of the following materials or conditions: heat and oxidizing materials.

Section 11. Toxicological Information

Toxicity data

United States

<u>Product/ingredient name</u>	<u>Test</u>	<u>Result</u>	<u>Route</u>	<u>Species</u>
Phosphoric Acid	LD50	1530 mg/kg	Oral	Rat
	LD50	1530 mg/kg	Oral	Rat
	LD50	2740 mg/kg	Dermal	Rabbit
	LD50	2740 mg/kg	Dermal	Rabbit
	LC50	850 mg/m ³ (1 hour/hours)	Inhalation	Rat
Ethanol	LD50	7060 mg/kg	Oral	Rat
	LD50	6300 mg/kg	Oral	Rabbit
	LD50	3450 mg/kg	Oral	Mouse
	LDLo	1400 mg/kg	Oral	human
	LDLo	5500 mg/kg	Oral	Dog

Section 11. Toxicological Information

Chronic effects on humans : **CARCINOGENIC EFFECTS** Classified A4 (Not classifiable for humans or animals.) by ACGIH [Ethanol].
Contains material which causes damage to the following organs: blood, the reproductive system, liver, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.

Other toxic effects on humans : Very hazardous in case of skin contact (corrosive, irritant, permeator), of eye contact (corrosive), of ingestion, of inhalation.

Specific effects

Carcinogenic effects : No known significant effects or critical hazards.

Mutagenic effects : No known significant effects or critical hazards.

Teratogenicity /
Reproductive toxicity : No known significant effects or critical hazards.

Sensitization

Ingestion : May cause burns to mouth, throat and stomach.

Inhalation : Corrosive to the respiratory system.

Eyes : Corrosive to eyes.

Skin : Corrosive to the skin.

Section 12. Ecological Information

Ecotoxicity data

United States

<u>Product/ingredient name</u>	<u>Species</u>	<u>Period</u>	<u>Result</u>
Ethanol	Daphnia magna (EC50)	48 hour/hours	2 mg/l
	Daphnia magna (EC50)	48 hour/hours	9.3 mg/l
	Daphnia magna (EC50)	48 hour/hours	>100 mg/l
	Daphnia magna (LC50)	96 hour/hours	>100 mg/l
	Pimephales promelas (LC50)	96 hour/hours	>100 mg/l
	Oncorhynchus mykiss (LC50)	96 hour/hours	13000 mg/l

Environmental precautions : No known significant effects or critical hazards.

Products of degradation : These products are carbon oxides (CO, CO₂) and water, phosphates.

Toxicity of the products of biodegradation : The products of degradation are less toxic than the product itself.

Section 13. Disposal Considerations


Waste disposal : The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

The information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

Section 14. Transport Information

Regulatory information	UN number	Proper shipping name	Class	PG*	Label	Additional information
DOT Classification	UN3265	CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (PHOSPHORIC ACID)	8	III		Not available.

PG* : Packing group

Section 15. Regulatory Information

United States

- HCS Classification** : Toxic material
Corrosive material
Target organ effects
- U.S. Federal regulations** : TSCA 8(b) inventory: Listed
SARA 302/304/311/312 extremely hazardous substances: No products were found.
SARA 302/304 emergency planning and notification: No products were found.
SARA 302/304/311/312 hazardous chemicals: Ethanol; Phosphoric Acid
SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Ethanol:
Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard;
Phosphoric Acid : Immediate (acute) health hazard
Clean Water Act (CWA) 307: No products were found.
Clean Water Act (CWA) 311: Phosphoric Acid
Clean Air Act (CAA) 112 accidental release prevention: No products were found.
Clean Air Act (CAA) 112 regulated flammable substances: No products were found.
Clean Air Act (CAA) 112 regulated toxic substances: No products were found.
- State regulations** : Pennsylvania RTK: Ethanol: (generic environmental hazard); Phosphoric Acid :
(environmental hazard, generic environmental hazard)
Massachusetts RTK: Ethanol; Phosphoric Acid
New Jersey: Water; Ethanol; Phosphoric Acid

Canada

- WHMIS (Canada)** : Class D-2B: Material causing other toxic effects (Toxic).
Class E: Corrosive material
- CEPA DSL/CEPA NDSL** : CEPA DSL: Water; Ethanol; Phosphoric Acid

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

EU regulations

Hazard symbol/symbols :



- Risk phrases** : R36/38- Irritating to eyes and skin.
- Safety phrases** : S2- Keep out of the reach of children.
S46- If swallowed, seek medical advice immediately and show this container or label.

International regulations


Section 15. Regulatory Information

International lists : Australia (NICNAS): Water; Coomassie Blue (TM) G-250; Ethanol; Phosphoric Acid
 China: Coomassie Blue (TM) G-250; Ethanol; Phosphoric Acid
 Germany water class: Ethanol; Phosphoric Acid
 Japan (METI): Water; Coomassie Blue (TM) G-250; Ethanol; Phosphoric Acid
 Korea (TCCL): Water; Coomassie Blue (TM) G-250; Ethanol; Phosphoric Acid
 Philippines (RA6969): Water; Coomassie Blue (TM) G-250; Ethanol; Phosphoric Acid

Section 16. Other Information

Label requirements : DANGER!
 CAUSES RESPIRATORY TRACT, EYE AND SKIN BURNS.
 HARMFUL IF INHALED OR SWALLOWED.
 CONTAINS MATERIAL WHICH CAUSES DAMAGE TO THE FOLLOWING ORGANS:
 BLOOD, REPRODUCTIVE SYSTEM, LIVER, RESPIRATORY TRACT, SKIN,
 CENTRAL NERVOUS SYSTEM, EYE, LENS OR CORNEA.

National Fire Protection Association (U.S.A.) :



Other special considerations : The Bradford Kit contains: Bradford Reagent, BSA Solution, and Sodium Chloride Solution. Information about Bradford Reagent is contained in this MSDS. BSA Solution and Sodium Chloride Solution are not hazardous and do not require a MSDS under OSHA 29 CFR 1910.1200 for the USA or WHMIS for Canada.

Notice to reader

The statements contained herein are based upon technical data that EMD Chemicals Inc. believes to be reliable, are offered for information purposes only and as a guide to the appropriate precautionary and emergency handling of the material by a properly trained person having the necessary technical skills. Users should consider these data only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use, storage and disposal of these materials and the safety and health of employees and customers and the protection of the environment. EMD CHEMICALS INC. MAKES NO REPRESENTATION OR WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE, WITH RESPECT TO THE INFORMATION HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS.