

SAFETY DATA SHEET

1. Identification

Product identifier: XYLENES

Other means of identification

Product No.: X516, 8802, 8668, 8664, 9516, 9493, 9490, 5377, 9483, 8118

Recommended use and restriction on use

Recommended use: Not determined.

Restrictions on use: Not determined.

Details of the supplier of the safety data sheet

	Avantor Performance Materials, LLC.
	3477 Corporate Parkway
	Center Valley, PA 18034
Telephone:	
	Customer Service: 855-282-6867
Fax:	610-573-2610
Contact Person:	Environmental Health & Safety
E-mail:	info@avantormaterials.com

Emergency telephone number:

CHEMTREC: 1-800-424-9300 within US and Canada

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids	Category 3
-------------------	------------

Health Hazards

Acute toxicity (Dermal)	Category 4
Acute toxicity (Inhalation - vapor)	Category 4
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2A
Carcinogenicity	Category 2
Specific Target Organ Toxicity - Single Exposure	Category 3 ¹
Specific Target Organ Toxicity - Repeated Exposure	Category 1 ²
Aspiration Hazard	Category 1

Target Organs

- 1.Narcotic effect., Respiratory tract irritation.
- 2.Central nervous system, Lungs, auditory organs

Unknown toxicity - Health

Acute toxicity, oral	0,08 %
----------------------	--------

Acute toxicity, dermal	0,08 %
Acute toxicity, inhalation, vapor	100 %
Acute toxicity, inhalation, dust or mist	100 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2
--	------------

Unknown toxicity - Environment

Acute hazards to the aquatic environment	0,07 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: Flammable liquid and vapor.
Harmful if swallowed, in contact with skin or if inhaled.
Causes skin irritation.
Causes serious eye irritation.
Suspected of causing cancer.
Causes damage to organs through prolonged or repeated exposure.

Toxic to aquatic life.

Precautionary Statements

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Wear protective gloves/protective clothing/eye protection/face protection. Wash hands thoroughly after handling.

Response: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting.

Other hazards which do not result in GHS classification: Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	Content in percent (%)*
XYLENES		1330-20-7	60 - 100%
ETHYL BENZENE		100-41-4	10 - 30%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

General information:	Get medical advice/attention if you feel unwell. Show this safety data sheet to the doctor in attendance.
Ingestion:	Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Inhalation:	Move to fresh air. Get medical attention if symptoms persist.
Skin Contact:	Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention if irritation persists after washing. Wash contaminated clothing before reuse.
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention if irritation persists after washing.

Most important symptoms/effects, acute and delayed

Symptoms:	Irritating to eyes, respiratory system and skin.
Hazards:	None known.

Indication of immediate medical attention and special treatment needed

Treatment:	Treat symptomatically. Symptoms may be delayed.
-------------------	---

5. Fire-fighting measures

General Fire Hazards:	Flammable liquid and vapor. In case of fire and/or explosion do not breathe fumes.
------------------------------	--

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:	Water spray, fog, CO ₂ , dry chemical, or alcohol resistant foam.
Unsuitable extinguishing media:	Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising from the chemical:	Vapors may cause a flash fire or ignite explosively. Vapors may travel considerable distance to a source of ignition and flash back. Heat may cause the containers to explode. Prevent buildup of vapors or gases to explosive concentrations.
--	--

Special protective equipment and precautions for firefighters

- Special fire fighting procedures:** Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.
- Special protective equipment for fire-fighters:** Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

- Personal precautions, protective equipment and emergency procedures:** ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). See Section 8 of the SDS for Personal Protective Equipment. Keep unauthorized personnel away. Keep upwind. Ventilate closed spaces before entering them. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Use personal protective equipment.
- Methods and material for containment and cleaning up:** In case of leakage, eliminate all ignition sources. Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Clean surface thoroughly to remove residual contamination. Dike far ahead of larger spill for later recovery and disposal. Take precautionary measures against static discharges. Use non-sparking tools. Stop leak if possible without any risk.
- Notification Procedures:** Prevent entry into waterways, sewer, basements or confined areas. Inform authorities if large amounts are involved.
- Environmental Precautions:** Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

- Precautions for safe handling:** Wash hands thoroughly after handling. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Do not breathe mist or vapor. Use only with adequate ventilation. Avoid contact with eyes. Avoid contact with skin.
- Conditions for safe storage, including any incompatibilities:** Keep away from food, drink and animal feeding stuffs. Keep container tightly closed. Store in a well-ventilated place. Ground container and transfer equipment to eliminate static electric sparks. Comply with all national, state, and local codes pertaining to the storage, handling, dispensing, and disposal of flammable liquids.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
XYLENES	STEL	150 ppm 651 mg/m ³	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	TWA	100 ppm 434 mg/m ³	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)

XYLENES	TWA	100 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
XYLENES	TWA	100 ppm		Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) (03 2011)
	STEL	150 ppm		Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) (03 2011)
XYLENES	TWA	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
XYLENES	8 HR ACL	100 ppm		Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
	15 MIN ACL	150 ppm		Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
XYLENES	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm	651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
XYLENES	TWA	100 ppm		US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm		US. ACGIH Threshold Limit Values (2011)
ETHYL BENZENE	STEL	125 ppm	543 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	TWA	100 ppm	434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
ETHYL BENZENE	TWA	20 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
ETHYL BENZENE	TWA	20 ppm		Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) (03 2011)
ETHYL BENZENE	STEL	125 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWA	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
ETHYL BENZENE	8 HR ACL	100 ppm		Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
	15 MIN ACL	125 ppm		Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
ETHYL BENZENE	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm	543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
ETHYL BENZENE	TWA	20 ppm		US. ACGIH Threshold Limit Values (2011)

Appropriate Engineering Controls

Use explosion-proof ventilation equipment to stay below exposure limits.

Individual protection measures, such as personal protective equipment

General information:	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. An eye wash and safety shower must be available in the immediate work area. Use explosion-proof ventilation equipment.
Eye/face protection:	Wear safety glasses with side shields (or goggles). Wear face shield if there is risk of splashes.
Skin Protection	
Hand Protection:	Chemical resistant gloves
Other:	Wear suitable protective clothing.
Respiratory Protection:	In case of inadequate ventilation use suitable respirator.
Hygiene measures:	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned. Provide eyewash station and safety shower. Wash hands before breaks and immediately after handling the product. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Wash contaminated clothing before reuse.

9. Physical and chemical properties

Appearance

Physical state:	Liquid
Form:	Liquid
Color:	Colorless
Odor:	Characteristic
Odor threshold:	No data available.
pH:	Not applicable
Melting point/freezing point:	-41,5 °C
Initial boiling point and boiling range:	139 °C
Flash Point:	29 °C
Evaporation rate:	No data available.
Flammability (solid, gas):	No data available.
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	7 %(V)
Flammability limit - lower (%):	1 %(V)
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	1,1 kPa
Vapor density:	No data available.
Density:	0,86 g/ml (20 °C)
Relative density:	0,86 (20 °C)
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.

Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	464 °C
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No dangerous reaction known under conditions of normal use.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	Hazardous polymerization does not occur.
Conditions to avoid:	Heat, sparks, flames. Contact with incompatible materials.
Incompatible Materials:	Strong oxidizing agents. Strong acids.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	Harmful if inhaled.
Skin Contact:	Harmful in contact with skin. Causes skin irritation.
Eye contact:	Causes serious eye irritation.
Ingestion:	May be harmful if swallowed.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral	
Product:	ATEmix (Rat): 4.125,89 mg/kg
Dermal	
Product:	ATEmix (Rabbit): 1.358,02 mg/kg
Inhalation	
Product:	No data available.
Specified substance(s):	
XYLENES	LC 50 (Rat): 12,1 mg/l

Repeated dose toxicity	
Product:	None known.

Skin Corrosion/Irritation	
Product:	Causes skin irritation.

Serious Eye Damage/Eye Irritation

Product: Causes serious eye irritation.

Respiratory or Skin Sensitization

Product: Not a skin sensitizer.

Carcinogenicity

Product: Suspected of causing cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

ETHYL BENZENE Overall evaluation: 2B. Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

ACGIH Carcinogen List:

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No mutagenic components identified

In vivo

Product: No mutagenic components identified

Reproductive toxicity

Product: May damage fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure

Product: Narcotic effect. Respiratory tract irritation.

Specific Target Organ Toxicity - Repeated Exposure

Product: Central nervous system. Lungs. auditory organs

Aspiration Hazard

Product: May be fatal if swallowed and enters airways.

Other effects:

None known.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

XYLENES

LC 50 (Bluegill (Lepomis macrochirus), 96 h): 10,464 - 13,762 mg/l Mortality
 LC 50 (Fathead minnow (Pimephales promelas), 96 h): 25,62 - 32,64 mg/l Mortality
 LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 6,7 - 10 mg/l Mortality

LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 13,41 mg/l Mortality
LC 50 (Rainbow trout, donaldson trout (*Oncorhynchus mykiss*), 96 h): 9,5 - 19,2 mg/l Mortality

ETHYL BENZENE LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 9,1 - 15,6 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 96 h): 93 - 211 mg/l Mortality
LC 50 (Carp (*Leuciscus idus melanotus*), 48 h): 44 mg/l Mortality

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

XYLENES LC 50 (Water flea (*Daphnia magna*), 24 h): 150 mg/l Mortality
LC 50 (Daggerblade grass shrimp (*Palaemonetes pugio*), 96 h): 7,4 mg/l Mortality
LC 50 (Calanoid copepod (*Diaptomus forbesi*), 96 h): 99,5 mg/l Mortality

ETHYL BENZENE EC 50 (Water flea (*Daphnia magna*), 48 h): 1,37 - 4,4 mg/l Intoxication
EC 50 (Brine shrimp (*Artemia sp.*), 48 h): 3,58 - 9,46 mg/l Intoxication
LC 50 (Water flea (*Daphnia magna*), 48 h): 10,6 - 17,2 mg/l Mortality
LC 50 (Brine shrimp (*Artemia sp.*), 48 h): 3,91 - 13,7 mg/l Mortality
LC 50 (Opossum shrimp (*Americamysis bahia*), 24 h): > 5,2 mg/l Mortality

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: There are no data on the degradability of this product.

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available on bioaccumulation.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

XYLENES Log Kow: 3,12 - 3,20

ETHYL BENZENE Log Kow: 3,15

Mobility in soil:

The product is insoluble in water and will spread on the water surface.

Other adverse effects:

Toxic to aquatic life.

13. Disposal considerations

Disposal instructions:	Discharge, treatment, or disposal may be subject to national, state, or local laws. Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging:	Since emptied containers retain product residue, follow label warnings even after container is emptied.

14. Transport information

TDG

UN Number:	UN 1307
UN Proper Shipping Name:	XYLENES
Transport Hazard Class(es)	
Class:	3
Label(s):	3
Packing Group:	III
Marine Pollutant:	No
Special precautions for user:	Not determined.

IMDG

UN Number:	UN 1307
UN Proper Shipping Name:	XYLENES
Transport Hazard Class(es)	
Class:	3
Label(s):	3
EmS No.:	F-E, S-D
Packing Group:	III
Marine Pollutant:	No
Special precautions for user:	Not determined.

IATA

UN Number:	UN 1307
UN Proper Shipping Name:	Xylenes
Transport Hazard Class(es):	
Class:	3
Label(s):	3
Packing Group:	III
Marine Pollutant:	No
Special precautions for user:	Not determined.
Cargo aircraft only:	Allowed.

Transport in bulk according to Annex II of MARPOL and the IBC Code: Not applicable

15. Regulatory information

Canada Federal Regulations

List of Toxic Substances (CEPA, Schedule 1)

Not Regulated

Export Control List (CEPA 1999, Schedule 3)

Not Regulated

National Pollutant Release Inventory (NPRI)

Canada. National Pollutant Release Inventory (NPRI) Substances, Part 5, VOCs with Additional Reporting Requirements

NPRI PT5 XYLENESToluene

Canada. National Pollutant Release Inventory (NPRI) (Schedule 1, Parts 1-4)
NPRI XYLENESETHYL
 BENZENE

Greenhouse Gases

Not Regulated

Controlled Drugs and Substances Act

CA CDSI	Not Regulated
CA CDSII	Not Regulated
CA CDSIII	Not Regulated
CA CDSIV	Not Regulated
CA CDSV	Not Regulated
CA CDSVII	Not Regulated
CA CDSVIII	Not Regulated

Precursor Control Regulations

Chemical Identity

Toluene

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

Inventory Status:

China Inv. Existing Chemical Substances:	On or in compliance with the inventory
Canada NDSL Inventory:	Not applicable
Japan ISHL Listing:	Not in compliance with the inventory.
Japan Pharmacopoeia Listing:	Not in compliance with the inventory.
EINECS, ELINCS or NLP:	On or in compliance with the inventory
Australia AICS:	On or in compliance with the inventory
Canada DSL Inventory List:	On or in compliance with the inventory
Japan (ENCS) List:	On or in compliance with the inventory
Korea Existing Chemicals Inv. (KECI):	On or in compliance with the inventory
Philippines PICCS:	On or in compliance with the inventory
US TSCA Inventory:	On or in compliance with the inventory
New Zealand Inventory of Chemicals:	On or in compliance with the inventory

16. Other information, including date of preparation or last revision
--

Revision Date: 18.05.2018

Version #: 2.1

Further Information: No data available.

Disclaimer: The information provided in this Safety Data Sheet (SDS) was prepared based on data believed to be accurate as of the date of this SDS. TO THE GREATEST EXTENT PERMITTED BY LAW, AVANTOR PERFORMANCE MATERIALS ("AVANTOR") EXPRESSLY DISCLAIMS ANY AND ALL REPRESENTATIONS AND WARRANTIES REGARDING THE INFORMATION CONTAINED HEREIN INCLUDING, WITHOUT LIMITATION, AS TO ACCURACY, COMPLETENESS, FITNESS FOR PURPOSE OR USE, MERCHANTABILITY, NON-INFRINGEMENT, PERFORMANCE, SAFETY, SUITABILITY AND STABILITY. This SDS is intended as a guide to the appropriate use, handling, storage and disposal of the product to which it relates by properly trained personnel, and is not intended to be comprehensive. Users of Avantor's products are advised to perform their own tests and to exercise their own judgment to determine the safety, suitability and appropriate use, handling, storage and disposal of each product and product combination for their own purposes and uses. TO THE GREATEST EXTENT PERMITTED BY LAW, AVANTOR DISCLAIMS LIABILITY FOR, AND BY USING AVANTOR'S PRODUCTS PURCHASER AGREES THAT UNDER NO CIRCUMSTANCES SHALL AVANTOR BE LIABLE FOR, SPECIAL, INDIRECT, INCIDENTAL, PUNITIVE OR CONSEQUENTIAL DAMAGES OF ANY TYPE OR KIND, INCLUDING WITHOUT LIMITATION, FOR LOSS OF PROFITS, REPUTATIONAL DAMAGE, PRODUCT RECALL OR BUSINESS INTERRUPTION.