



FEEL THE SW  
DIFFERENCE.®

# DESIGNED TO ENHANCE WORKER PERFORMANCE.



**PF-95LG**

POWDER-FREE ECOTEK BIODEGRADABLE  
NITRILE SINGLE-USE GLOVES WITH ENERGEL\*

**ECOTEK BIODEGRADABLE GLOVE THAT  
COMBINES TACTILE SENSITIVITY WITH ENERGEL  
TECHNOLOGY TO SOOTHE AND HYDRATE SKIN\***

- EnerGel® Hand Conditioning Technology hydrates and soothes skin
- EcoTek® Biodegradability Technology accelerates landfill breakdown without any performance loss
- Tested for use with chemotherapy drugs
- Optimal thickness for durability and tactile sensitivity
- Fully textured surface for excellent wet and dry grip
- Silicone-free to prevent contamination
- Tear-resistant beaded cuff eases donning
- SHA Dermatologically Approved
- 1.5 AQL exceeds laboratory standards



Optimal thickness  
for durability and  
tactile sensitivity

Fully textured  
surface for wet  
and dry grip

Tear-resistant  
beaded cuff for  
easy donning

**PF** **PF-95LG**

WEIGHT	LENGTH	THICKNESS	FEATURES	COLOR
7.0g (large size)	9.5"	5.1 mil	EnerGel® EcoTek®	LIGHT GREEN

ECOTEK



## TECHNICAL DATA



### PF-95LG

POWDER-FREE ECOTEK BIODEGRADABLE  
NITRILE SINGLE-USE GLOVES WITH ENERCEL\*

## PRODUCT DESCRIPTION

### SPECIFICATIONS

<b>PRODUCT</b>	PowerForm®		
<b>GRADE</b>	Powder-Free Exam		
<b>MATERIAL</b>	Nitrile		
<b>THICKNESS</b>	<b>FINGER</b>	5.9mil	0.15mm
	<b>PALM</b>	5.1mil	0.13mm
	<b>CUFF</b>	4.0mil	0.10mm
<b>COLOR</b>	Light Green		
<b>SURFACE</b>	<b>OUTER</b>	Fully Textured	
	<b>INNER</b>	EnerGel®	
<b>LENGTH</b>	9.5"	242mm	
<b>WEIGHT</b>	7.0 g		
<b>FIT TYPE</b>	Ambidextrous		
<b>CUFF TYPE</b>	Beaded		
<b>WATERTIGHT AQL</b>	1.5		
<b>ORIGIN COUNTRY</b>	China		

\* Specifications based on size Large glove

### PHYSICAL PROPERTIES

	PRE-AGING	POST-AGING
<b>TENSILE STRENGTH:</b>	14 MPa	14 MPa
<b>ELONGATION:</b>	500%	400%

### INTEGRATED TECHNOLOGIES

**ENERCEL** Hand Conditioning Technology: allows for thorough penetration of aloe vera into the skin, reduces water loss to retain moisture and has been clinically proven to prevent many skin ailments, like dermatitis.

**ECOTEK** Biodegradability Technology: 92.6% biodegradable in 2.5 years. ASTM D5526-12 test results do not predict future biodegradation.\*



## STANDARDS & CERTIFICATIONS

EN ISO 21420:2020	EU 2016/425
EN 455-2000-2015	CAT III Complex Design
ASTM D6319-19	UL NFPA 1999-2018
ASTM D6978-05 (2019)	FDA 21 CFR 177.2600
ASTM F1671-13	
ASTM F739-12	
Reach EU 1907/2006	

CE 0493



EN ISO 374-1:2016/TYPE B



EN ISO 3745:2016



Please visit [swsafety.com/symbols](http://swsafety.com/symbols) for information on standards used on this document.

## ORDERING

ITEM NO.	SIZE	PALM WIDTH	PACKAGING
N129401	XS 5½ – 6	3.0" 75mm	100 gloves per box 10 boxes per case
N129402	S 6½ – 7	3.1" 80mm	100 gloves per box 10 boxes per case
N129403	M 7½ – 8	3.4" 87mm	100 gloves per box 10 boxes per case
N129404	L 8½ – 9	4.0" 101mm	100 gloves per box 10 boxes per case
N129405	XL 9½ – 10	4.5" 114mm	100 gloves per box 10 boxes per case
N129406	2XL 10½ – 11	4.8" 123mm	100 gloves per box 10 boxes per case

## APPLICATIONS

### INDUSTRIAL

- Assembly
- Cleaning
- Handling and Packaging Devices
- Liquid Handling
- Oily or Wet Surfaces
- Painting

### MEDICAL

- Chemical Handling
- Clinical
- Laboratory
- Light Chemical Mixing
- Pharma Production

Keep out of sunlight. Store in a cool, dry place.  
Keep away from sources of ozone or ignition.



R\_N12940X1121



\*Under test method ASTM D5526-12, a standard test method for determining anaerobic biodegradation of plastics in accelerated landfill conditions. Current biodegradation results do not predict future results.