Product Name:	VWR-HC-49-TS
Description:	VWR Catalog No: 76580-162
	VWR Performance Series Glass Door Laboratory Refrigerator
	49 Cu. Ft. capacity
	Two swing glass doors, self-closing (energy efficient, double pane vacuum
	insulated)
	Microprocessor temperature controller
	Adjustable operating temperature range: 1°C - 10°C
	Touch Screen Digital Temperature Display and Alarm Module
	Password-protected control panel
	Sample simulated digital temperature display; .1° Resolution, adjustable
	temperature display in Celsius or Fahrenheit
	Active temperature scale bar display
	Resettable 1-point min/max history
	Digital 24-hour temperature chart
	Temperature data logging
	USB port for data transfer and software updates
	Real-time operational display clock
	4-20mA output
	Electronic troubleshooting guide
	Electronic QR Code to access Owner's Manual & technical support contact
	Information
	Adjustable alarm volume
	Audible and visual high/low temperature alarms
	Sensor error alarm
	Power failure alarm
	Door ajar alarm
	Low battery alarm
	Operation indicator
	Alarm validation (audible, visual, and remote alarm)
	Alarm mute with ring back
	Remote alarm contacts
	Eight adjustable shelves (adjustable in ½" increments)
	Forced draft air circulation
	Keyed door lock
	Magnetic door gasket for positive seal
	Heavy duty door handles
	LED interior lights are safety shielded and switch controlled
	Swivel casters (adds 4" to height)
	Probe access port (3/8")
	White laminated vinyl exterior
	White aluminum liner and stainless steel floor interior
	HFC-free refrigerant (R290), foam insulation and packaging
	Three year parts and labor warranty, plus an additional two year compressor
	parts warranty
	Exterior dimensions: 54 1/4"W x 31"D x 78 5/8"H without casters; 82 5/8" H
	with casters
	Cycle defrost
	115V, 60 Hz, 8.5 Amps, 1/2 HP, BTU/HR 7315
	UL/C-UL listed
	Shipping weight: 495 lbs.