



MATERIAL SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Revision Date 08/22/2013

Version 1.1

SECTION 1. Identification

Product identifier

Product number 101777
Product name Petroleum benzine boiling range 80-100°C for analysis EMSURE®

Relevant identified uses of the substance or mixture and uses advised against

Identified uses Reagent for analysis

Details of the supplier of the safety data sheet

Company EMD Millipore Corporation | 290 Concord Road, Billerica, MA 01821, United States of America | SDS Phone Support: +1-978-715-1335 | General Inquiries: +1-978-715-4321 | Monday to Friday, 9:00 AM to 4:00 PM Eastern Time (GMT-5)

Emergency telephone 800-424-9300 CHEMTREC (USA)
+1-703-527-3887 CHEMTREC (International)
24 Hours/day; 7 Days/week

SECTION 2. Hazards identification

GHS Classification

Flammable liquid, Category 2, H225
Aspiration hazard, Category 1, H304
Chronic aquatic toxicity, Category 2, H411

For the full text of the H-Statements mentioned in this Section, see Section 16.

GHS-Labeling

Hazard pictograms



Signal Word

Danger

Hazard Statements

H225 Highly flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements

MATERIAL SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number 101777
Product name Petroleum benzine boiling range 80-100°C for analysis EMSURE®

Version 1.1

P210 Keep away from heat.
P273 Avoid release to the environment.
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
P331 Do NOT induce vomiting.

OSHA Hazards

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Other hazards

None known.

SECTION 3. Composition/information on ingredients

Chemical nature Mixture of diverse liquid hydrocarbons.
Benzene content < 0.1%
CAS-No. 64742-49-0

Hazardous ingredients

Chemical Name (Concentration)

CAS-No.

naphtha (petroleum), hydrotreated light (80-100°C) (>= 90 % - <= 100 %)
64742-49-0

SECTION 4. First aid measures

Description of first-aid measures

Inhalation

After inhalation: fresh air. Consult doctor if feeling unwell.

Skin contact

After skin contact: wash off with plenty of water. Remove contaminated clothing.

Eye contact

After eye contact: rinse out with plenty of water with the eyelid held wide open. Call in ophthalmologist if necessary.

Ingestion

If swallowed Caution Aspiration hazard Keep respiratory tract clear. Call a physician immediately. Subsequently administer: activated charcoal (20 - 40 g in 10% slurry). No milk. No digestible oils. In case of spontaneous vomiting: Risk of aspiration. Pulmonary failure possible. Call in physician.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed

irritant effects, respiratory paralysis, Dizziness, Unconsciousness, agitation, spasms, cardiovascular disorders, Headache

It generally applies for aliphatic hydrocarbons with 6 - 18 carbon atoms that they may cause pneumonia, in some cases also pulmonary oedema, upon direct inhalation, i.e. in conditions that can occur only in very special circumstances (nebulizations, spraying, inhalation of aerosols and similar). After absorption of very large quantities: narcosis.

Indication of any immediate medical attention and special treatment needed

MATERIAL SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number

101777

Version 1.1

Product name

Petroleum benzene boiling range 80-100°C for analysis EMSURE®

No information available.

SECTION 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂), Foam, Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

Special hazards arising from the substance or mixture

Combustible material, Vapors are heavier than air and may spread along floors.

Forms explosive mixtures with air at ambient temperatures.

Pay attention to flashback.

Development of hazardous combustion gases or vapors possible in the event of fire.

Advice for firefighters

Special protective equipment for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Further information

Prevent fire extinguishing water from contaminating surface water or the ground water system.

Cool closed containers exposed to fire with water spray.

SECTION 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Avoid substance contact. Do not breathe vapors, aerosols. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert.

Advice for emergency responders: Protective equipment see section 8.

Environmental precautions

Do not empty into drains. Risk of explosion.

Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills.

Observe possible material restrictions (see sections 7 and 10).

Take up with liquid-absorbent material (e.g. Chemisorb®). Dispose of properly. Clean up affected area.

SECTION 7. Handling and storage

Precautions for safe handling

Observe label precautions.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Conditions for safe storage, including any incompatibilities

MATERIAL SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number

101777

Version 1.1

Product name

Petroleum benzine boiling range 80-100°C for analysis EMSURE®

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Store at +15°C to +25°C (+59°F to +77°F).

SECTION 8. Exposure controls/personal protection

Exposure limit(s)

Contains no substances with occupational exposure limit values.

Engineering measures

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment.

Individual protection measures

Protective clothing should be selected specifically for the workplace, depending on concentration and quantity of the hazardous substances handled. The chemical resistance of the protective equipment should be inquired at the respective supplier.

Hygiene measures

Immediately change contaminated clothing. Apply skin- protective barrier cream. Wash hands and face after working with substance.

Eye/face protection

Safety glasses

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Other protective equipment:

Flame retardant antistatic protective clothing

Respiratory protection

required when vapors/aerosols are generated.

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

SECTION 9. Physical and chemical properties

Physical state	liquid
Color	colorless
Odor	characteristic
Odor Threshold	No information available.
pH	No information available.
Melting point	No information available.
Boiling point/boiling range	176 - 212 °F (80 - 100 °C) at 1,013 hPa

MATERIAL SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number 101777 Version 1.1
Product name Petroleum benzine boiling range 80-100°C for analysis EMSURE®

Flash point	< -6 °F (< -21 °C)
Evaporation rate	No information available.
Flammability (solid, gas)	No information available.
Lower explosion limit	1.0 %(V)
Upper explosion limit	6.5 %(V)
Vapor pressure	ca. 60 hPa at 68 °F (20 °C)
Relative vapor density	No information available.
Relative density	0.69 g/cm ³ at 68 °F (20 °C)
Water solubility	at 77 °F (25 °C) insoluble
Partition coefficient: n-octanol/water	No information available.
Autoignition temperature	No information available.
Decomposition temperature	No information available.
Viscosity, dynamic	No information available.
Explosive properties	No information available.
Ignition temperature	ca. 482 °F (250 °C)
Viscosity, kinematic	0.6 mm ² /s at 68 °F (20 °C)

SECTION 10. Stability and reactivity

Reactivity

Vapors may form explosive mixture with air.

Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

Possibility of hazardous reactions

Violent reactions possible with:

Strong oxidizing agents

Conditions to avoid

Warming.

A range from approx. 15 Kelvin below the flash point is to be rated as critical.

MATERIAL SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number

101777

Version 1.1

Product name

Petroleum benzene boiling range 80-100°C for analysis EMSURE®

Incompatible materials

rubber, various plastics

Hazardous decomposition products

no information available

SECTION 11. Toxicological information

Information on toxicological effects

Likely route of exposure

Inhalation, Eye contact, Skin contact

Target Organs

Eyes

Skin

Respiratory system

Central nervous system

Acute oral toxicity

LD50 rat: > 5,000 mg/kg (External MSDS)

Acute inhalation toxicity

LC50 rat: 3400 ppm; 4 h (RTECS)

Symptoms: Irritation symptoms in the respiratory tract.

Acute dermal toxicity

LD50 rabbit: > 3,000 mg/kg

(External MSDS)

Skin irritation

Drying-out effect resulting in rough and chapped skin. Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Eye irritation

slight irritation

Specific target organ systemic toxicity - single exposure

The substance or mixture is not classified as specific target organ toxicant, single exposure.

Specific target organ systemic toxicity - repeated exposure

The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Aspiration hazard

Aspiration hazard, Aspiration may cause pulmonary edema and pneumonitis.

Carcinogenicity

IARC

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

MATERIAL SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number	101777	Version 1.1
Product name	Petroleum benzine boiling range 80-100°C for analysis EMSURE®	

NTP	No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
ACGIH	No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

Further information

After absorption:

Headache, Dizziness, agitation, spasms, Unconsciousness

Cannot be excluded:

cardiovascular disorders, respiratory paralysis

Other information

It generally applies for aliphatic hydrocarbons with 6 - 18 carbon atoms that they may cause pneumonia, in some cases also pulmonary oedema, upon direct inhalation, i.e. in conditions that can occur only in very special circumstances (nebulizations, spraying, inhalation of aerosols and similar). After absorption of very large quantities: narcosis.

Further data:

Handle in accordance with good industrial hygiene and safety practice.

SECTION 12. Ecological information

Ecotoxicity

No information available.

Persistence and degradability

Biodegradability

Not readily biodegradable.

Bioaccumulative potential

No information available.

Mobility in soil

No information available.

Additional ecological information

We have no quantitative data concerning the ecological effects of this product.

Biological effects:

Endangers drinking-water supplies if allowed to enter soil or water.

Further information on ecology

Separation via an oil extractor.

Discharge into the environment must be avoided.

SECTION 13. Disposal considerations

The information presented only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations. Disposal should be in accordance with applicable regional, national and local laws and regulations.

MATERIAL SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number 101777 Version 1.1
Product name Petroleum benzine boiling range 80-100°C for analysis EMSURE®

SECTION 14. Transport information

Land transport (DOT)

UN number UN 1268
Proper shipping name PETROLEUM DISTILLATES, N.O.S. (PETROLEUM SPIRIT)
Class 3
Packing group II
Environmentally hazardous --

Air transport (IATA)

UN number UN 1268
Proper shipping name PETROLEUM DISTILLATES, N.O.S.
Class 3
Packing group II
Environmentally hazardous --
Special precautions for user no

Sea transport (IMDG)

UN number UN 1268
Proper shipping name PETROLEUM DISTILLATES, N.O.S. (PETROLEUM SPIRIT)
Class 3
Packing group II
Environmentally hazardous --
Special precautions for user yes
EmS F-E S-E

SECTION 15. Regulatory information

United States of America

OSHA Hazards

Flammable Liquid
Target organ effects

This information is based on 29 CFR 1910.1200 criteria prior to adoption of the GHS, and may deviate from the GHS information on the label and in section 2.

SARA 311/312 Hazards

Fire Hazard
Chronic Health Hazard

SARA 313

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 302

MATERIAL SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number
Product name

101777
Petroleum benzine boiling range 80-100°C for analysis EMSURE®

Version 1.1

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

DEA List I

Not listed

DEA List II

Not listed

US State Regulations

Massachusetts Right To Know

Remarks

No components are subject to the Massachusetts Right to Know Act.

Pennsylvania Right To Know

Ingredients

naphtha (petroleum), hydrotreated light (80-100°C)

New Jersey Right To Know

Ingredients

naphtha (petroleum), hydrotreated light (80-100°C)

California Prop 65 Components

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

Notification status

TSCA: All components of the product are listed in the TSCA-inventory.

DSL: All components of this product are on the Canadian DSL.

SECTION 16. Other information

Training advice

Provide adequate information, instruction and training for operators.

Full text of H-Statements referred to under sections 2 and 3.

H225 Highly flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H411 Toxic to aquatic life with long lasting effects.

Key or legend to abbreviations and acronyms used in the safety data sheet

MATERIAL SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number

101777

Version 1.1

Product name

Petroleum benzine boiling range 80-100°C for analysis EMSURE®

Used abbreviations and acronyms can be looked up at www.wikipedia.org.

Revision Date 08/22/2013

The information contained herein is based on the present state of our knowledge. It characterizes the product with regard to appropriate safety precautions. It does not represent a warranty of any product properties and we assume no liability for any loss or injury which may result from the use of this information. Users should conduct their own investigations to determine the suitability of the information.

All rights reserved. Millipore and the "M" Mark are registered trademarks of Merck KGaA, Darmstadt, Germany.