

Heptane

BDH1127

Version 1.4 Revision Date 03/25/2015 Print Date 05/08/2015

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Heptane

MSDS Number : 000000011719

Product Use Description : Solvent

Manufactured for : VWR International LLC

Radnor Corporate Center

Building One Suite 200

100 Matsonford Road Radnor PA 19087

For more information call : (Monday-Friday, 8.00am-5:00pm)

1-800-932-5000

In case of emergency call : (24 hours/day, 7 days/week)

1-800-424-9300(USA Only)

For Transportation Emergencies:

1-800-424-9300 (CHEMTREC - Domestic) 1-613-996-6666 (CANUTEC - Canada)

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Form : liquid, clear

Color : colourless

Odor : hydrocarbon-like

Page 1 / 15



Heptane

BDH1127

Print Date 05/08/2015 Version 1.4 Revision Date 03/25/2015

Classification of the substance or mixture

or mixture

Classification of the substance : Flammable liquids, Category 2 Skin irritation, Category 2

Specific target organ toxicity - single exposure, Category 3,

Central nervous system Aspiration hazard, Category 1

GHS Label elements, including precautionary statements

Symbol(s)







Signal word : Danger

Hazard statements : Highly flammable liquid and vapour.

May be fatal if swallowed and enters airways.

Causes skin irritation.

May cause drowsiness and dizziness.

: Prevention: Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No

smokina.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ ventilating/ lighting/ equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

Wash skin thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/ eye protection/ face protection.

Response:

IF SWALLOWED: Immediately call a POISON CENTER or

doctor/ physician.

IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

IF INHALED: Remove victim to fresh air and keep at rest in a



Heptane

BDH1127

Version 1.4 Revision Date 03/25/2015 Print Date 05/08/2015

position comfortable for breathing.

Call a POISON CENTER or doctor/ physician if you feel unwell.

Do NOT induce vomiting.

If skin irritation occurs: Get medical advice/ attention.

Take off contaminated clothing and wash before reuse.

In case of fire: Use dry sand, dry chemical or alcohol-resistant

In case of fire: Use dry sand, dry chemical or alcohol-resistation for extinction.

Storage:

Store in a well-ventilated place. Keep container tightly closed.

Keep cool. Store locked up.

Disposal:

Dispose of contents/container in accordance with local, state &

federal regulations.

Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Formula : C7H16

Chemical nature : Substance

Chemical Name	CAS-No.	Concentration
Heptane	142-82-5	100.00 %

SECTION 4. FIRST AID MEASURES

Inhalation : Call a physician immediately. Remove to fresh air. If not

breathing, give artificial respiration. If breathing is difficult, give oxygen. Use oxygen as required, provided a qualified operator is

Page 3 / 15



Heptane

BDH1127

Version 1.4 Revision Date 03/25/2015 Print Date 05/08/2015

present.

Skin contact : Wash off immediately with plenty of water for at least 15

minutes. Take off contaminated clothing and shoes immediately. Wash contaminated clothing before re-use. Call a physician.

Eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Call a physician.

Ingestion : Do not induce vomiting without medical advice. If a person

vomits when lying on his back, place him in the recovery position. Call a physician immediately. Never give anything by

mouth to an unconscious person.

Notes to physician

Treatment : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Foam

Carbon dioxide (CO2)

Dry chemical

Cool closed containers exposed to fire with water spray.

Unsuitable extinguishing

media

: Do not use a solid water stream as it may scatter and spread

fire.

Specific hazards during

firefighting

: Flammable.

Vapours may form explosive mixtures with air.

Vapours are heavier than air and may spread along floors. Vapors may travel to areas away from work site before

igniting/flashing back to vapor source.

In case of fire hazardous decomposition products may be

produced such as: Carbon monoxide Carbon dioxide (CO2)

Special protective equipment : Wear self-contained breathing apparatus and protective suit.

Page 4 / 15



Heptane

BDH1127

Version 1.4 Revision Date 03/25/2015 Print Date 05/08/2015

for firefighters

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear personal protective equipment. Unprotected persons

must be kept away.

Immediately evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Ensure adequate ventilation. Remove all sources of ignition.

Do not swallow.

Do not breathe vapours or spray mist. Avoid contact with skin, eyes and clothing.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Prevent product from entering drains.

Discharge into the environment must be avoided.

Do not flush into surface water or sanitary sewer system. Do not allow run-off from fire fighting to enter drains or water

courses.

Methods for cleaning up : Ventilate the area.

No sparking tools should be used. Use explosion-proof equipment.

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national

regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Handling

Handling : Wear personal protective equipment.

Use only in well-ventilated areas. Keep container tightly closed.

Do not smoke. Do not swallow.

Page 5 / 15



Heptane

BDH1127

Version 1.4 Revision Date 03/25/2015 Print Date 05/08/2015

Do not breathe vapours or spray mist. Avoid contact with skin, eyes and clothing.

Advice on protection against :

fire and explosion

Keep away from fire, sparks and heated surfaces.

Take precautionary measures against static discharges.

Ensure all equipment is electrically grounded before beginning

transfer operations.

Use explosion-proof equipment.

Keep product and empty container away from heat and sources

of ignition.

No sparking tools should be used.

No smoking.

Storage

Requirements for storage areas and containers

Store in area designed for storage of flammable liquids. Protect

from physical damage.

Keep containers tightly closed in a dry, cool and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Keep away from heat and sources of ignition.

Keep away from direct sunlight.

Store away from incompatible substances.

Container hazardous when empty.

Do not pressurize, cut, weld, braze, solder, drill, grind or expose

containers to heat or sources of ignition.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective measures : Ensure that eyewash stations and safety showers are close to

the workstation location.

Engineering measures : Use with local exhaust ventilation.

Prevent vapour buildup by providing adequate ventilation during

and after use.

Eye protection : Do not wear contact lenses.

Wear as appropriate:

Page 6 / 15



Heptane

BDH1127

Version 1.4 Revision Date 03/25/2015 Print Date 05/08/2015

Safety glasses with side-shields If splashes are likely to occur, wear:

Goggles or face shield, giving complete protection to eyes

Hand protection : Solvent-resistant gloves

Gloves must be inspected prior to use.

Replace when worn.

Skin and body protection : Wear as appropriate:

Solvent-resistant apron

Flame retardant antistatic protective clothing.

If splashes are likely to occur, wear:

Protective suit

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory

equipment.

For rescue and maintenance work in storage tanks use

self-contained breathing apparatus.

Use NIOSH approved respiratory protection.

Hygiene measures : When using do not eat, drink or smoke.

Wash hands and face before breaks and immediately after

handling the product.

Keep working clothes separately.

Remove and wash contaminated clothing before re-use.

Do not swallow.

Do not breathe vapours or spray mist. Avoid contact with skin, eyes and clothing.

Exposure Guidelines

Exposure duracinies					
Components	CAS-No.	Value	Control parameters	Upda te	Basis
Heptane	142-82-5	STEL: Short term exposure limit	(500 ppm)	02 2012	ACGIH:US. ACGIH Threshold Limit Values

Heptane	142-82-5	TWA:	(400 ppm)	02	ACGIH:US. ACGIH
		time		2012	Threshold Limit
		weighted			Values
		average			



Heptane

BDH1127

Version 1.4	Revision Date 03/25/2015	Print Date 05/08/2015

Heptane	142-82-5	Ceil Tim	1,800 mg/m3	2005	NIOSH/GUIDE:US.
Першие	142-02-3	e : Ceiling Limit Value		2003	NIOSH: Pocket Guide to Chemical Hazards
		and Time Period (if specified)			
Llantona	142-82-5	REL:	250 mg/m2	2005	NIOSH/GUIDE:US.
Heptane	142-62-3	Recomm ended exposure limit (REL):	350 mg/m3 (85 ppm)	2005	NIOSH/GOIDE.OS. NIOSH: Pocket Guide to Chemical Hazards
	140.00.5	IDEL .	0.000/0	100	COLIA TRANCILIO
Heptane	142-82-5	PEL: Permissi ble exposure limit	2,000 mg/m3 (500 ppm)	02 2006	OSHA_TRANS:US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)
Llontono	142-82-5	TWA:	1,600 mg/m3	1989	Z1A:US. OSHA
Heptane	142-82-3	time weighted average	(400 ppm)	1969	Table Z-1-A (29 CFR 1910.1000)
Hantona	140.00.5	OTEL .	0.000/0	1,000	714.110 00114
Heptane	142-82-5	STEL : Short	2,000 mg/m3 (500 ppm)	1989	Z1A:US. OSHA Table Z-1-A (29
		term exposure			CFR 1910.1000)

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid, clear

Page 8 / 15



Heptane

BDH1127

Version 1.4 Revision Date 03/25/2015 Print Date 05/08/2015

Color : colourless

Odor : hydrocarbon-like

pH : Note: Not applicable

Melting point/freezing point : -90.6 ℃

Boiling point/boiling range : 98.4 ℃

Flash point : $25 \, ^{\circ}\text{F} \, (-4 \, ^{\circ}\text{C})$

Method: closed cup

Evaporation rate : ca. 4.00

Method: Compared to Butyl acetate.

Lower explosion limit : 1 %(V)

Upper explosion limit : 6.70 %(V)

Vapor pressure : 47.33 hPa

Vapor density : 3.5 Note: (Air = 1.0)

Density : 0.684 g/cm3 at 20 ℃

Water solubility : 0.003 g/l at 25 °C



Heptane

BDH1127

Version 1.4 Revision Date 03/25/2015 Print Date 05/08/2015

Ignition temperature : 204 ℃

Molecular weight : 100.21 g/mol

SECTION 10. STABILITY AND REACTIVITY

Possibility of hazardous

Conditions to avoid

reactions

: Hazardous polymerisation does not occur.

: Heat, flames and sparks. Keep away from direct sunlight.

Incompatible materials to

avoid

: Oxidizing agents

Phosphorus

Chlorine

May attack many plastics, rubbers and coatings.

Hazardous decomposition

products

: Stable under normal conditions.

In case of fire hazardous decomposition products may be

produced such as: Carbon monoxide Carbon dioxide (CO2)

SECTION 11. TOXICOLOGICAL INFORMATION

Acute inhalation toxicity : LC50: 103 mg/l

Exposure time: 4 h Species: Rat

: LC50: > 29.29 mg/l, vapour

Exposure time: 4 h Species: Rat

Method: OECD Test Guideline 403

Note: No deaths

Page 10 / 15



Heptane

BDH1127

Version 1.4 Revision Date 03/25/2015 Print Date 05/08/2015

Skin irritation : Result: Irritating to skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity effects

Toxicity to fish : LC50: 2,940 mg/l

Exposure time: 48 h

Species: Leuciscus idus (Golden orfe)

: LC50: 4.0 mg/l Exposure time: 24 h

Species: Carassius auratus (goldfish)

: LC50: 4,900 mg/l Exposure time: 24 h

Species: Gambusia affinis (Mosquito fish)

Toxicity to daphnia and other : static test

aquatic invertebrates

EC50: 1.5 mg/l

Exposure time: 48 h

Species: Daphnia (water flea)

Further information on ecology

Additional ecological

information

: Very toxic to aquatic organisms, may cause long-term adverse

effects in the aquatic environment. Not inherently biodegradable.

The product can be accumulated in water organisms. Do not flush into surface water or sanitary sewer system.

SECTION 13. DISPOSAL CONSIDERATIONS



Heptane

BDH1127

Version 1.4 Revision Date 03/25/2015 Print Date 05/08/2015

Disposal methods : Dispose of contents/ container in accordance with local, state,

and federal regulations.

SECTION 14. TRANSPORT INFORMATION

DOT UN/ID No. : UN 1206

Proper shipping name : HEPTANES

Class 3 Packing group II Hazard Labels 3

IATA UN/ID No. : UN 1206

Description of the goods : HEPTANES

Class : 3
Packaging group : II
Hazard Labels : 3
Packing instruction (cargo : 364

aircraft)

Packing instruction : 353

(passenger aircraft)

Packing instruction : Y341

(passenger aircraft)

IMDG UN/ID No. : UN 1206

Description of the goods : HEPTANES

Class : 3
Packaging group : II
Hazard Labels : 3

EmS Number : F-E, S-D Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

Inventories

US. Toxic Substances

: On TSCA Inventory

Control Act

Page 12 / 15



Heptane

BDH1127

Version 1.4 Revision Date 03/25/2015 Print Date 05/08/2015

Australia. Industrial

Chemical (Notification and

Assessment) Act

: On the inventory, or in compliance with the inventory

Canada. Canadian **Environmental Protection**

Act (CEPA). Domestic Substances List (DSL) : All components of this product are on the Canadian DSL.

Japan. Kashin-Hou Law List : On the inventory, or in compliance with the inventory

Korea. Toxic Chemical Control Law (TCCL) List : On the inventory, or in compliance with the inventory

Philippines. The Toxic Substances and Hazardous

and Nuclear Waste Control

Act

: On the inventory, or in compliance with the inventory

Chemical Substances

China. Inventory of Existing : On the inventory, or in compliance with the inventory

New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New

Zealand

: On the inventory, or in compliance with the inventory

National regulatory information

SARA 302 Components : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

: This material does not contain any chemical components with **SARA 313 Components**

> known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards : Fire Hazard

> Acute Health Hazard Chronic Health Hazard



Heptane

BDH1127

Version 1.4 Revision Date 03/25/2015 Print Date 05/08/2015

California Prop. 65 : This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other

reproductive harm.

Massachusetts RTK : Heptane 142-82-5

New Jersey RTK : Heptane 142-82-5

Pennsylvania RTK : Heptane 142-82-5

WHMIS Classification : B2: Flammable liquid

D2B: Toxic Material Causing Other Toxic Effects

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required

by the CPR.

SECTION 16. OTHER INFORMATION

	HMIS III	NFPA
Health hazard	: 1*	1
Flammability	: 3	3
Physical Hazard	: 0	
Instability	:	0

^{* -} Chronic health hazard

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information



Heptane

BDH1127

Version 1.4 Revision Date 03/25/2015 Print Date 05/08/2015

and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Previous Issue Date: 06/18/2012

Prepared by Honeywell Performance Materials and Technologies Product Stewardship Group