

## PYREX® Serialized/Certified Volumetric Glassware

Now tested and calibrated in an ISO/IEC 17025 certified laboratory

The accuracy of volumetric glassware can have a significant impact on experimental and testing results. This is why quality glassware is made in compliance with ASTM or industry recognized standards. In fact, PYREX glassware has long been, and will continue to be, made to ASTM standards.

But now we've taken our glassware quality control to an even higher level. As an added assurance of accuracy and precision, PYREX volumetric glassware is now tested and calibrated in an ISO/IEC 17025 accredited laboratory.

### The Measure of Glassware Accuracy

To be ISO/IEC 17025 certified, an accredited laboratory must demonstrate high levels of competency for testing and calibration. ISO/IEC 17025 accreditation is your assurance that our laboratory has the appropriate quality management systems and technical competence to accurately and precisely test and calibrate your glassware.

### Eliminates the Need for Third Party Testing

PYREX volumetric glassware will now be available with the laboratory ISO/IEC 17025 certificate, which can eliminate the need for independent third party calibration testing. Certificates can be downloaded from [www.corning.com/certificates](http://www.corning.com/certificates).

### Another Milestone in a 100-year Legacy

ISO/IEC 17025 accreditation is the latest chapter in the PYREX story of continuous improvement and innovation. Invented by Corning in 1915, PYREX's chemically stable, heat-resistant, low-expansion borosilicate formula has been at the heart of groundbreaking discoveries and advancements in medicine, chemistry, and countless other fields. For more information, visit [www.corning.com/pyrex](http://www.corning.com/pyrex).

### Available for a Variety of Glassware

Volumetric PYREX glassware tested and calibrated in accordance with ISO/IEC 17025 includes:

- ▶ Burets
- ▶ Volumetric flasks
- ▶ Volumetric and serological pipets
- ▶ Graduated cylinders

See inside for a product listing.



Volumetric  
Glassware  
ISO/IEC 17025  
Certified Laboratory

### 2105 PYREX® Buret, Serialized/Certified Class A, Colored Scale, PTFE Stopcock Plug



VWR Cat. No.	Corning Cat. No.	Approx. Capacity (mL)	Grad. Increment (mL)	Tol.* (± mL)	Approx. O.D. x Height (mm)	Qty/Cs
17473-075	2105-10	10	.05	.02	9 x 560	1
17473-078	2105-25	25	.10	.03	12 x 560	1
77776-974	2105-50	50	.10	.05	14 x 750	1
17473-084	2105-100	100	.20	.10	18 x 752	1

### 2135 PYREX Buret, Serialized/Certified, Class A, Precision Bore, Straight § Stopcock



VWR Cat. No.	Corning Cat. No.	Approx. Capacity (mL)	Grad. Increment (mL)	Tol. (± mL)	Approx. O.D. x Height (mm)	§ Stopcock** Bore (mm)	Qty/Cs
17473-087	2135-10	10	.05	.02	9 x 560	2	1
17473-090	2135-25	25	.10	.03	12 x 560	2	1
17473-093	2135-50	50	.10	.05	14 x 755	2	1
17473-096	2135-100	100	.20	.10	18 x 752	2	1

### 3002 PYREX Cylinder, Serialized/Certified, Class A, Single Metric Scale, Graduated, Calibrated To Contain, § PYREX Stopper



VWR Cat. No.	Corning Cat. No.	Capacity (mL)	Grad. Increment (mL)	ASTM Tol. (± mL)	Approx. O.D. x Height (mm)	§ Stopper No.	Qty/Cs
24768-024	3002-10	10	0.1	.10	13 x 195	9	1
24768-046	3002-25	25	0.2	.17	18 x 225	13	1
24768-068	3002-50	50	1.0	.25	24 x 255	16	1
24768-090	3002-100	100	1.0	.50	29 x 295	16	1
24768-104	3002-250	250	2.0	1.0	39 x 385	22	1
24768-126	3002-500	500	5.0	2.0	50 x 445	27	1
24768-148	3002-1L	1000	10.0	3.0	64 x 520	32	1
24768-150	3002-2L	2000	20.0	6.0	83 x 550	38	1

### 3062 PYREX Cylinder, Serialized/Certified, Class A, Single Metric Scale, Graduated, Calibrated To Deliver



VWR Cat. No.	Corning Cat. No.	Capacity (mL)	Grad. Increment (mL)	ASTM Tol. (± mL)	Approx. O.D. x Height (mm)	Pk/Cs	Qty/Cs
24714-025	3062-10	10	0.1	0.10	13 x 178	1	1
24714-047	3062-25	25	0.2	0.17	18 x 192	1	1
24714-069	3062-50	50	1.0	0.25	24 x 225	1	1
24714-091	3062-100	100	1.0	0.50	29 x 254	1	1
24714-105	3062-250	250	2.0	1.0	39 x 340	1	1
24714-127	3062-500	500	5.0	2.0	50 x 390	1	1
24714-149	3062-1L	1000	10.0	3.0	64 x 465	1	1
24714-151	3062-2L	2000	20.0	6.0	83 x 520	1	1

### 55680 PYREX Flask, Low Actinic, Volumetric, Class A, Certified/Serialized, PYREX § Stopper



VWR Cat. No.	Corning Cat. No.	Description	Capacity (mL)	Tol. (± mL)	Approx. O.D. x Height (mm)	§ Stopper No.	Qty/Cs
89090-086	55680-10	Complete	10	0.02	28 x 99	9	1
89090-094	55680-25	Complete	25	0.03	40 x 122	9	1
89090-102	55680-50	Complete	50	0.05	51 x 152	9	1
89090-084	55680-100	Complete	100	0.08	60 x 182	13	1
89090-090	55680-200	Complete	200	0.10	74 x 214	13	1
89090-092	55680-250	Complete	250	0.12	78 x 253	16	1
89090-100	55680-500	Complete	500	0.20	100 x 288	19	1
89090-088	55680-1L	Complete	1000	0.30	125 x 344	22	1
89090-096	55680-2L	Complete	2000	0.50	158 x 390	27	1

\*Tol. = tolerance.

\*\*§ = Standard taper. Designates interchangeable joints, stoppers, and stopcocks that comply with the requirements of Commercial Standard CS-21 published by N.I.S.T.



### 5631 PYREX® Flask, Volumetric, Class A, Corning Certified and Serialized, Micro, PYREX § Stopper

VWR Cat. No.	Corning Cat. No.	Capacity (mL)	Tol.* (± mL)	Approx. O.D x Height (mm)	§ Stopper No.**	Qty/Cs
77777-070	5631-1	1	0.01	8 x 68	8	6
77777-074	5631-2	2	.015	12 x 71	8	6
77777-072	5631-10	10	0.02	20 x 105	9	6
77777-076	5631-25	25	0.03	29 x 132	9	6


For stoppers only, see VWR Cat. No. xxx (Corning Cat. No. 7650).



### 5680 PYREX Flask, Volumetric, Class A, Corning Certified and Serialized, PYREX § Stopper

VWR Cat. No.	Corning Cat. No.	Description	Capacity (mL)	Tol. (± mL)	Approx. O.D x Height (mm)	§ Stopper No.	Qty/Cs
29624-015	5680-10	Complete	10	0.02	28 x 99	9	1
29624-022	5680-25	Complete	25	0.03	40 x 122	9	1
29624-043	5680-50	Complete	50	0.05	51 x 152	9	1
29624-065	5680-100	Complete	100	0.08	60 x 182	13	1
29624-087	5680-200	Complete	200	0.10	74 x 214	13	1
29624-102	5680-250	Complete	250	0.12	78 x 253	16	1
29624-123	5680-500	Complete	500	0.20	100 x 288	19	1
29624-145	5680-1L	Complete	1000	0.30	125 x 344	22	1
29624-167	5680-2L	Complete	2000	0.50	158 x 390	27	1

### 7070 PYREX Pipet, Reusable Glass, Serialized/Certified, Class A, Colored Markings, Measuring, Color-coded, Calibrated To Deliver



VWR Cat. No.	Corning Cat. No.	Approx. Capacity (mL)	Grad. Increment (mL)	Tol. (± mL)	Approx. O.D x Length (mm)	Qty/Pk	Qty/Cs
53044-730	7070-1	1.0	0.1	.01	7 x 325	2	6
53044-732	7070-2	2.0	0.1	.01	7 x 350	2	6
53044-734	7070-5	5.0	0.1	.02	8 x 350	2	6
53044-736	7070-10	10.0	0.1	.03	10 x 380	2	6
53044-738	7070-25	25.0	0.1	.05	14 x 440	2	6

### 7101 PYREX Pipet, Serialized/Certified, Class A, Volumetric, Color-coded, Colored Graduations



VWR Cat. No.	Corning Cat. No.	Color Code	Capacity (mL)	Tol. (± mL)	Approx. Length (mm)	Qty/Pk	Qty/Cs
89091-226	7101-1	Blue	1.0	.006	313	2	6
89091-304	7101-2	Orange	2.0	.006	333	2	6
89091-364	7101-3	Black	3.0	.01	356	2	6
89091-392	7101-4	Red	4.0	.01	370	2	6
89091-490	7101-5	White	5.0	.01	392	2	6
89091-122	7101-10	Red	10.0	.02	429	2	6
89091-178	7101-15	Green	15.0	.03	445	2	6
89091-234	7101-20	Yellow	20.0	.03	516	2	6
89091-270	7101-25	Blue	25.0	.03	521	2	6
89091-466	7101-50	–	50.0	.05	516	2	6
89091-082	7101-100	–	100.0	.08	565	2	6

Do not pipet by mouth. We suggest using a mechanical pipetting device.

\*Tol. = tolerance.

\*\*§ = Standard taper. Designates interchangeable joints, stoppers, and stopcocks that comply with the requirements of Commercial Standard CS-21 published by N.I.S.T.

**7103C PYREX® Pipet, Serialized/Certified, Class A, Volumetric, Color-coded, Colored Graduations, Calibrated To Contain, Calibrated To Deliver**



VWR Cat. No.	Corning Cat. No.	Color Code	Capacity (mL)	Tol.* (± mL)	Approx. Length (mm)	Qty/Pk	Qty/Cs
46610-102	7103C-1	Blue	1.0	.006	313	2	6
46610-104	7103C-2	Orange	2.0	.006	333	2	6
46610-106	7103C-3	Black	3.0	.01	356	2	6
46610-108	7103C-4	Red	4.0	.01	370	2	6
46610-110	7103C-5	White	5.0	.01	392	2	6
46610-112	7103C-6	Orange	6.0	.01	420	2	6
46610-114	7103C-7	Green	7.0	.01	420	2	6
46610-116	7103C-8	Blue	8.0	.02	425	2	6
46610-118	7103C-9	Black	9.0	.02	425	2	6
46610-120	7103C-10	Red	10.0	.02	429	2	6
46610-122	7103C-15	Green	15.0	.03	445	2	6
46610-124	7103C-20	Yellow	20.0	.03	516	2	6
46610-126	7103C-25	Blue	25.0	.03	521	2	6

Do not pipet by mouth. We suggest using a mechanical pipetting device.  
\*Tol. = tolerance.

**Warranty/Disclaimer:** Unless otherwise specified, all products are for research use only. Not intended for use in diagnostic or therapeutic procedures. Corning Life Sciences makes no claims regarding the performance of these products for clinical or diagnostic applications.

CORNING | FALCON | AXYGEN | GOSSELIN | PYREX



1.800.932.5000 | [vwr.com](http://vwr.com)

Prices and product details are current when published; subject to change without notice. | Certain products may be limited by federal, state, provincial, or local regulations. | VWR makes no claims or warranties concerning sustainable/green products. Any claims concerning sustainable/green products are the sole claims of the manufacturer and not those of VWR International, LLC. All prices are in US dollars unless otherwise noted. Offers valid in US and Canada, void where prohibited by law or company policy, while supplies last. | VWR, the VWR logo and variations on the foregoing are registered (®) or unregistered trademarks and service marks, of VWR International, LLC and its related companies. All other marks referenced are registered by their respective owner(s). | Visit [vwr.com](http://vwr.com) to view our privacy policy, trademark owners and additional disclaimers. ©2016 VWR International, LLC. All rights reserved.