

**SILASTIC(R) Q7-4765 BIOMEDICAL GRADE ETR ELASTOMER, PART A (PART A information is below)****1. PRODUCT AND COMPANY IDENTIFICATION**

Dow Corning Corporation  
South Saginaw Road  
Midland, Michigan 48686

**24 Hour Emergency Telephone: (989) 496-5900**

Customer Service: (989) 496-6000

Product Disposal Information: (989) 496-6315

CHEMTREC: (800) 424-9300

MSDS No.: 02662396

Revision Date: 2013/08/22

Generic Description: Silicone  
Physical Form: Rubber-Crepe  
Color: Tan  
Odor: Not available

NFPA Profile: Health 0 Flammability 1 Instability/Reactivity 0

Note: NFPA = National Fire Protection Association

**2. HAZARDS IDENTIFICATION****POTENTIAL HEALTH EFFECTS****Acute Effects**

Eye: No significant irritation expected from a single exposure.  
Skin: No significant irritation expected from a single short-term exposure.  
Inhalation: No significant effects expected from a single short-term exposure.  
Oral: Low ingestion hazard in normal use.

**Prolonged/Repeated Exposure Effects**

Skin: No known applicable information.  
Inhalation: No known applicable information.  
Oral: No known applicable information.

**Signs and Symptoms of Overexposure**

No known applicable information.

**Medical Conditions Aggravated by Exposure**

No known applicable information.

**SILASTIC(R) Q7-4765 BIOMEDICAL GRADE ETR ELASTOMER, PART A (PART A information is below)**

The above listed potential effects of overexposure are based on actual data, results of studies performed upon similar compositions, component data and/or expert review of the product. Please refer to Section 11 for the detailed toxicology information.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

None present. This is not a hazardous material as defined in the OSHA Hazard Communication Standard.

**4. FIRST AID MEASURES**

Eye:	No effects expected. If irritation occurs, flush eye(s) with lukewarm gently flowing water for 5 minutes. If irritation persists, obtain medical advice.
Skin:	No health effects expected. If irritation does occur flush with lukewarm, gently flowing water for 5 minutes. If irritation persists, obtain medical advice.
Inhalation:	If symptoms are experienced remove source of contamination or move victim to fresh air. If irritation persists, obtain medical advice.
Oral:	If irritation or discomfort occur, obtain medical advice.
Notes to Physician:	Treat according to person's condition and specifics of exposure.

**5. FIRE FIGHTING MEASURES**

Flash Point:	Not applicable.
Autoignition Temperature:	Not determined.
Flammability Limits in Air:	Not determined.
Extinguishing Media:	On large fires use dry chemical, foam or water spray. On small fires use carbon dioxide (CO <sub>2</sub> ), dry chemical or water spray. Water can be used to cool fire exposed containers.
Fire Fighting Measures:	Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals. Use water spray to keep fire exposed containers cool. Determine the need to evacuate or isolate the area according to your local emergency plan.
Unusual Fire Hazards:	None.

**6. ACCIDENTAL RELEASE MEASURES**

**SILASTIC(R) Q7-4765 BIOMEDICAL GRADE ETR ELASTOMER, PART A (PART A information is below)**

Containment/Clean up: Observe all personal protection equipment recommendations described in Sections 5 and 8. Collect and contain for salvage or disposal. Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

Note: See Section 8 for Personal Protective Equipment for Spills. Call (989) 496-5900, if additional information is required.

**7. HANDLING AND STORAGE**

Use with adequate ventilation.

Use reasonable care and store away from oxidizing materials.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION****Component Exposure Limits**

There are no components with workplace exposure limits.

**Engineering Controls**

Local Ventilation: None should be needed.  
General Ventilation: Recommended.

**Personal Protective Equipment for Routine Handling**

Eyes: Use proper protection - safety glasses as a minimum.  
Skin: Washing at mealtime and end of shift is adequate.  
Suitable Gloves: Handle in accordance with good industrial hygiene and safety practices.  
Inhalation: No respiratory protection should be needed.  
Suitable Respirator: None should be needed.

**Personal Protective Equipment for Spills**

Eyes: Use proper protection - safety glasses as a minimum.

**SILASTIC(R) Q7-4765 BIOMEDICAL GRADE ETR ELASTOMER, PART A (PART A information is below)**

Skin:	Washing at mealtime and end of shift is adequate.
Inhalation/Suitable Respirator:	No respiratory protection should be needed.
Precautionary Measures:	Use reasonable care.
Comments:	When heated to temperatures above 150°C (300°F) in the presence of air, product can form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Vapors irritate eyes, nose, and throat. Safe handling conditions may be maintained by keeping vapor conditions within the OSHA permissible exposure limit for formaldehyde.

Note: These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

Physical Form:	Rubber-Crepe
Color:	Tan
Odor:	Not available
Specific Gravity @ 25°C:	1.2
Viscosity:	Not determined.
Freezing/Melting Point:	Not determined.
Boiling Point:	Not determined.
Vapor Pressure @ 25°C:	Not determined.
Vapor Density:	Not determined.
Solubility in Water:	Not determined.
pH:	Not determined.
Volatile Content:	Not determined.
Flash Point:	Not applicable.
Autoignition Temperature:	Not determined.
Flammability Limits in Air:	Not determined.

Note: The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

**10. STABILITY AND REACTIVITY**

Chemical Stability:	Stable.
Hazardous Polymerization:	Hazardous polymerization will not occur.
Conditions to Avoid:	None.
Materials to Avoid:	Oxidizing material can cause a reaction.

**SILASTIC(R) Q7-4765 BIOMEDICAL GRADE ETR ELASTOMER, PART A (PART A information is below)**Hazardous Decomposition Products

Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Carbon oxides and traces of incompletely burned carbon compounds. Silicon dioxide. Formaldehyde.

**11. TOXICOLOGICAL INFORMATION**Special Hazard Information on Components

No known applicable information.

**12. ECOLOGICAL INFORMATION**Environmental Fate and Distribution

- Air:** This product is a solid consisting of a high molecular weight silicone polymer and other solid materials. Unless milled to produce a dust or particles, it is unlikely to give rise to atmospheric contamination.
- Water:** This product is a solid which is completely insoluble in water. As the specific gravity is >1, it will sink to the bottom of the water course.
- Soil:** This product will enter the terrestrial environment if, as a component of municipal or industrial solid waste the product is landfilled. It is unlikely that further significant transformation of the product will occur.
- Degradation:** High molecular weight polymer which is amenable to recycling. The product is not biodegradable. The product is removed >80% during the sewage treatment process.

Environmental Effects

- Toxicity to Water Organisms:** This product has low water solubility and should not present a risk to aquatic organisms.
- Toxicity to Soil Organisms:** This product is a solid and does not contain significant concentrations of water soluble constituents that may be leached from the product. It is therefore not likely to present a danger to terrestrial organisms.
- Bioaccumulation:** This product is a solid which is not soluble in water and if ingested will not be absorbed.

Fate and Effects in Waste Water Treatment Plants

This product is a solid rubber type material which is unlikely to have any adverse effect on bacteria.

**SILASTIC(R) Q7-4765 BIOMEDICAL GRADE ETR ELASTOMER, PART A (PART A information is below)**

## Ecotoxicity Classification Criteria

Hazard Parameters (LC50 or EC50)	High	Medium	Low
Acute Aquatic Toxicity (mg/L)	<=1	>1 and <=100	>100
Acute Terrestrial Toxicity	<=100	>100 and <= 2000	>2000

This table is adapted from "Environmental Toxicology and Risk Assessment", ASTM STP 1179, p.34, 1993.

This table can be used to classify the ecotoxicity of this product when ecotoxicity data is listed above. Please read the other information presented in the section concerning the overall ecological safety of this material.

**13. DISPOSAL CONSIDERATIONS****RCRA Hazard Class (40 CFR 261)**

When a decision is made to discard this material, as received, is it classified as a hazardous waste? No

State or local laws may impose additional regulatory requirements regarding disposal. Call (989) 496-6315, if additional information is required.

**14. TRANSPORT INFORMATION****DOT Road Shipment Information (49 CFR 172.101)**

Not subject to DOT.

**Ocean Shipment (IMDG)**

Not subject to IMDG code.

**Air Shipment (IATA)**

Not subject to IATA regulations.

Call Dow Corning Transportation, (989) 496-8577, if additional information is required.

**15. REGULATORY INFORMATION**

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Status: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

**EPA SARA Title III Chemical Listings****Section 302 Extremely Hazardous Substances (40 CFR 355):**

None.

**SILASTIC(R) Q7-4765 BIOMEDICAL GRADE ETR ELASTOMER, PART A (PART A information is below)****Section 304 CERCLA Hazardous Substances (40 CFR 302):**

None.

**Section 311/312 Hazard Class (40 CFR 370):**Acute: No  
Chronic: No  
Fire: No  
Pressure: No  
Reactive: No**Section 313 Toxic Chemicals (40 CFR 372):**

None present or none present in regulated quantities.

Note: Chemicals are listed under the 313 Toxic Chemicals section only if they meet or exceed a reporting threshold.

**Supplemental State Compliance Information****California**

Warning: This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm.

None known.

**New Jersey**

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
68083-19-2	40.0 - 60.0	Dimethyl siloxane, dimethylvinyl-terminated
7631-86-9	30.0 - 50.0	Silicon dioxide
70131-67-8	7.0 - 13.0	Dimethyl siloxane, hydroxy-terminated
68083-18-1	5.0 - 10.0	Dimethyl, methylvinyl siloxane, dimethylvinyl-terminated

**Pennsylvania**

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
68083-19-2	40.0 - 60.0	Dimethyl siloxane, dimethylvinyl-terminated
7631-86-9	30.0 - 50.0	Silicon dioxide

**SILASTIC(R) Q7-4765 BIOMEDICAL GRADE ETR ELASTOMER, PART A (PART A information is below)**

70131-67-8	7.0 - 13.0	Dimethyl siloxane, hydroxy-terminated
68083-18-1	5.0 - 10.0	Dimethyl, methylvinyl siloxane, dimethylvinyl-terminated

**16. OTHER INFORMATION**

Prepared by: Dow Corning Corporation

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

(R) indicates Registered Trademark