| Product Name: | VWR-HC-26-TS |
|---------------|---|
| Description: | VWR Catalog No: 76580-158 |
| | VWR Performance Series Glass Door Laboratory Refrigerator |
| | 26 Cu. Ft. capacity |
| | One swing glass door, self-closing (energy efficient, double pane vacuum |
| | insulated), right hinged, not reversible |
| | Microprocessor temperature controller |
| | Adjustable operating temperature range: 1°C - 10°C |
| | Touch Screen Digital Temperature Display and Alarm Module |
| | Password-protected control panel |
| | Sample simulated digital temperature display; .1° Resolution, adjustable |
| | temperature display in Celsius or Fahrenheit |
| | Active temperature scale bar display |
| | Resettable 1-point min/max history |
| | Digital 24-hour temperature chart |
| | Temperature data logging |
| | USB port for data transfer and software updates |
| | Real-time operational display clock |
| | 4-20mA output |
| | Electronic troubleshooting guide |
| | Electronic QR Code to access Owner's Manual & technical support contact |
| | Information |
| | Adjustable alarm volume |
| | Audible and visual high/low temperature alarms |
| | Sensor error alarm |
| | Power failure alarm |
| | Door ajar alarm |
| | Low battery alarm |
| | Operation indicator |
| | Alarm validation (audible, visual, and remote alarm) |
| | Alarm mute with ring back |
| | Remote alarm contacts |
| | Four adjustable shelves (adjustable in ½" increments) |
| | Forced draft air circulation |
| | Keyed door lock |
| | Magnetic door gasket for positive seal |
| | Recessed door handle |
| | LED interior lights are safety shielded and switch controlled |
| | Swivel casters (adds 4" to height) |
| | Probe access port (3/8") |
| | White laminated vinyl exterior |
| | White aluminum liner and stainless steel floor interior |
| | HFC-free refrigerant (R290), foam insulation and packaging |
| | Three year parts and labor warranty, plus an additional two year compressor |
| | parts warranty |
| | Exterior dimensions: 30"W x 30 1/2"D x 78 %"H without casters; 82 5/8"H |
| | with casters |
| | Cycle defrost |
| | 115V, 60 Hz, 5.4 Amps, 1/3 HP, BTU/HR 4932 |
| | UL/C-UL listed |
| | Shipping weight: 345 lbs. |