

Product Specification

Meets U.S.P Requirements, Meets B.P. Chemical Specifications, Meets E.P. Chemical Specifications, Meets J.P. Chemical Specifications, GMP Manufactured Product

Test	Specification
USP – Identification	Passes Test
USP – Congealing Temperature	$\geq 15.6\text{ }^{\circ}\text{C}$
USP – Nonvolatile Residue (USP), mg/20 mL	≤ 1.0
USP – Chloride (Cl)	Passes Test
USP – Sulfate (SO ₄)	Passes Test
USP – Readily Oxidizable Substances	Passes Test
USP – Assay (CH ₃ COOH)	99.5 – 100.5 %
EP/BP – Identification A	Passes Test
EP/BP – Identification B	Passes Test
EP/BP – Appearance	Passes Test
EP/BP – Freezing Point	$\geq 14.8\text{ }^{\circ}\text{C}$
EP/BP – Iron (Fe)	$\leq 5\text{ ppm}$
EP/BP – Chloride (Cl)	$\leq 25\text{ ppm}$
EP/BP – Sulfate (SO ₄)	$\leq 50\text{ ppm}$
EP/BP – Reducing Substances	Passes Test
EP/BP – Residue on Evaporation	$\leq 0.01\text{ %}$
EP/BP – Assay (CH ₃ COOH)	99.0 – 100.5 %
JP – Assay (CH ₃ COOH)	99.0 – 101.0 %
JP – Identification	Passes Test
JP – Congealing Point	$\geq 14.5\text{ }^{\circ}\text{C}$
JP – Nonvolatile Residue, mg/10 mL	≤ 1.0
JP – Chloride (Cl)	Passes Test
JP – Sulfate (SO ₄)	Passes Test
JP – Heavy Metals (as Pb)	$\leq 10\text{ ppm}$
JP – Reducing Substances	Passes Test

Acetic Acid, Glacial, U.S.P.
Multi-Compendial



Material No.: 9526-07

Test

Specification

GMP Manufactured Product

Bulk Pharmaceutical Chemical

CAUTION: For Manufacturing, processing or repackaging

Residual Solvents: No Class 1, 2 or 3 residual solvents are used in or produced by the production process.

Preserve in tight containers, and store at room temperature

Elemental Impurities (USP 232, EP 5.20) – Information on elemental impurities for this product is available on the associated Product Regulatory Data Sheet and elemental impurity profile report.

Storage Condition: IMPORTANT: Material will freeze if stored below 17 °C (63°F).

Packaging Site: Phillipsburg Mfg Ctr & DC

Jamie Ethier
Vice President Global Quality

For questions on this Product Specification please contact Technical Services at 855.282.6867 or +1.610.386.1700

Avantor Performance Materials, LLC

100 Matsonford Rd, Suite 200, Radnor, PA 19087. U.S.A. Phone 610.386.1700