



Technical Data Sheet

VWR® Ultra-Low Temperature Freezer

Revision: 0

VWR International, LLC, 100 Matsonford Rd, Radnor, PA 19087

ENERGY STAR®



Model Number

VWR50086GA (VWR Cat# 77618-774)

Application and Rating

Application	Storage of General (non-flammable) Laboratory Materials
Storage Volume	24.09 cu. ft. (682 liters), 500 Standard 2" Boxes
Temperature Rating	-50°C to -86°C
Electrical Power	100V - 230V 50/60Hz
Instrument Rated Current	8.9A - 4.9A (115V 60hz 8.4A, 208-230V 60hz 4.1A)
Recommended Building Supply Rating	Type C circuit protection or similar required, Ensure compliance with local electric code
Power Plug / Power Cord	Country Dependent Plug / IEC Cords, 10 ft (3.05 m)
Agency Listings	UL, cUL, CE, Energy Star
Application Environment	Non-Corrosive, Non-Flammable, Non-Explosive Indoor Use Only, Ventilated 15 - 32°C (59 - 90°F) < 60% RH

Dimensions and Construction

Interior Dimensions (H x D x W)	51.2 x 28.3 x 28.8 in. (1300 x 719 x 732 mm)
Exterior Dimensions (H x D x W)	78 x 37 x 34 in. (1981 x 940 x 864 mm)
Shipping Dimensions	83 x 45 x 47 in. (2108 x 1143 x 1194 mm)
Shipping Weight / Net Weight	749 / 655 lbs (340 / 297 kg)
Insulation	Vacuum Insulation Panels with High-Density Water-Blown Polyurethane Foam, Electric Heater at Breaker Area
Door	Single Outer: Silicone-Based Gasket Seal Number of Inner: 2x Stainless Steel
Shelves	3x Stainless Steel Adjustable Shelves in 1" (25 mm) Increments
Shelf Capacity	Shelf: 205 lbs / 93 kg Cabinet Load not to Exceed: 1140 lbs (517 kg)
Casters	4x Standard All-Direction with Locks

Electrical System Configuration

Power Switch	Main Circuit Breaker (Behind Grill Door)
Controller Type	7-segment Display with Capacitive Touch Screen Buttons with USB Data Retrieval at Eye Level
Control Security	Setpoint Setting, Passcode Access Control
Control Sensor	Single RTD (1000 ohm Platinum RTD, class B, -196°C)
Remote Outputs	RS485, 4-20 mA Output, Remote Warning Dry Contacts
Adjustable Warm/Cold Alarms	Adjustable in 1°C Increments


Refrigeration Configuration

Refrigeration System	Two Stage Cascade System
Compressor/Number	Variable Speed Industrial Rated, Hermetically Sealed / 2
Refrigerant (1st/2nd Stage)	R290 / R170 + R290 Mix
Flammable	Yes

Performance

Ambient	°C	20
Setpoint	°C	-80
Energy Consumption	kWh/day	8.0
Heat Rejection Rate	Btu/h (W)	1137 (333)
Peak Variation from Setpoint	°C	-3/1
Average Uniformity	°C	4.0
Average Stability	°C	<0.5
Average Cabinet Temperature	°C	-81.1
1min Door Opening Recovery to -75°C	min	16
Pull Down Time to -80°C	min	251
Warm Up Time -80°C to -50°C	min	268
Energy star rating	kwh/day/cuft	0.31
Sound Pressure Level	dB(A)	44

Dimensions in inch [metric in: mm]



1) Data is representative of performance and not published product specifications. Technical data sheet test results should not be referenced in developing any regulatory parameters for specific customer usage.
 2) Freezer performance will vary based on customer product volume, storage format, options selected, operating conditions, test methodology and performing recommended maintenance.
 3) Continuous product enhancements may, without notice, result in amendments or omissions to this technical data sheet. VWR International, LLC cannot accept responsibility for damage, injury, loss or expenses resulting from misapplication of the information herein.
 4) Actual temperature measurement will vary based on type and location of the probe used.

© 2019 Avantor, Inc. All rights reserved. All trademarks are the property of Avantor Inc. and its subsidiaries. Specifications, terms and pricing are subject to change.

Not all products are available in all countries. Please consult your local sales representative for details.