Description: Corepoint Scientific™ White Diamond Series Countertop Refrigerator Freestanding 1 Cu. Ft. Capacity One glass swing door, right hinged* Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts Remote alarm contacts	Product Name:	PR011WWG/0
Refrigerator Freestanding 1 Cu. Ft. Capacity One glass swing door, right hinged* Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms		
2 probes; 1 in air and 1 in glycol bottle Adjustable operating temperature range: 1°C – 10°C 2 adjustable shelves Back wall evaporator cover Forced draft circulation Keyed door lock Integrated door handle Magnetic door gasket for positive seal Leveling legs LED interior light Probe access port (3/8") Powder coat exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R600a), foam insulation and packaging Three year parts and labor warranty, plus an additional two year compressor parts only warranty Pyxis [®] , Omnicell [®] and AcuDose RX [®] compatible Exterior dimensions: 17 ¼" W x 19 ¼" D x 21 ¼"H Note: This unit must have 4" clearance on sides and back for adequate ventilation Cycle defrost 115V, 60 Hz, .90 Amps, 1/8 HP UL/C-UL listed Shipping weight: 91 lbs. *This product is available left hinged, product number		Corepoint Scientific [™] White Diamond Series Countertop Refrigerator Freestanding 1 Cu. Ft. Capacity One glass swing door, right hinged* Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts 2 probes; 1 in air and 1 in glycol bottle Adjustable operating temperature range: 1°C – 10°C 2 adjustable operating temperature range: 1°C – 10°C 2 adjustable shelves Back wall evaporator cover Forced draft circulation Keyed door lock Integrated door handle Magnetic door gasket for positive seal Leveling legs LED interior light Probe access port (3/8") Powder coat exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R600a), foam insulation and packaging Three year parts and labor warranty, plus an additional two year compressor parts only warranty Pyxis®, Omnicell® and AcuDose RX [®] compatible Exterior dimensions: 17 ¼" W x 19 ¼" D x 21 ¼"H <i>Note: This unit must have 4" clearance on sides and back for</i> <i>adequate ventilation</i> Cycle defrost 115V, 60 Hz, .90 Amps, 1/8 HP UL/C-UL listed Shipping weight: 91 lbs.