®A registered trademark of The Orange-Sol Group of Companies, Ltd.

Section 1 Product and Company Identification

Product Name:	De-Solv-it® Multi-Use Solvent/Citrus Solvent
Product Use:	General surface cleaning of oil, tar, mastic, gum, wax and adhesive residues
PIN Number:	Not required
Distributor:	Orange-Sol Industrial Products, Inc.
	1400 Fiesta Blvd., Bldg. 100
	Gilbert, AZ 85233-1000
Emergency Phone:	800-279-8822 (7 am – 4 pm, Mon-Fri MST)
For Information:	800-279-8822 (7 am – 4 pm, Mon-Fri MST)
Prepared by:	J.A. Gurney, Ph.D.
Preparation Date:	19 August 1991

Section 2 Composition Information on Ingredients

Hazardous Components: No hazardous ingredients as per OSHA 1910.1200

Section 3 Health and Physical Data

Emergency Overview:	Acute and prolonged exposure may cause dermatitis in a sensitive individual.	
Primary Routes of Entry:	Skin and mouth	
Physical Hazard:	Combustible mixture	
Health Hazard:	No acute of chronic hazards known	
Acute Hazards:		
Eye:	Contact nonirritating	
Skin:	Low primary skin irritation	
Ingestion:	If swallowed, may cause a laxative effect. Not considered hazardous	
Inhalation:	No toxic manifestations	
Chronic Exposure:		
Skin:	Repeated or prolonged exposure may cause dermatitis in a sensitive	
individual		
Carcinogenicity Listings: NTP-None, IARC-None, OSHA-None, ACGIH-None		
Irritancy of Product: Low primary skin irritancy. No eye or inhalation effects		
Signs & Symptoms of Overexposure: None known in normal individuals		
Medical Conditions Aggravated by Exposure: A preexisting dermatitis may become aggravated in a sensitive individual		

Section 4 First Aid Procedures

Eye:	Remove any contact lens, then immediately flush with water for at least 15 minutes. If
	irritation persists, contact a physician.
Skin:	Remove contaminated clothing. Wash skin thoroughly with soap and water. If irritation
	persists, contact a physician.
Ingestion:	If swallowed, do not induce vomiting. May be harmful or fatal if liquid is aspirated into
	the lungs.
Inhalation:	If aspirated into the lungs, get immediate medical help.

Section 5 Fire and Explosion Hazard

Flammability:	Combustible liquid. OSHA Class IIA. WHMIS Class B3.
Means of Extinction:	Water fog, carbon dioxide, dry chemical, foam
Flash Point and Method:	162°F (72°C), PMCC ASTM D-93
Flammability Limits in Air:	UEL 18%, LEL Not known, ASTM E-681
Auto-Ignition Temperature:	675°F, ASTM E-659
Combustion Products:	As with any organic material, combustion will produce carbon dioxide
	and/or carbon monoxide.
Explosion Data:	A. Sensitivity to impact: none B. Sensitivity to static charge: none
Special Firefighting Precauti	ons: Do not use streams of water. This may cause spattering and the
	spread of fire.
Unusual Fire and Explosion	Hazard: May produce dense, black smoke. Stay upwind of a fire.
Firefighting Equipment:	Use self-contained breathing apparatus (SCBA) gear in any
	enclosed space.

Section 6 Accidental Release Measures

Procedures for Clean-Up:	
For small spills:	Absorb with a suitable material. Dispose in an appropriate waste container.
For large spills:	Dike with soil, sand or other suitable materials avoiding the use of sawdust.
Personal Precautions:	Review Section 5 and 8 for precautions and recommendations. Remove all sources of ignition before proceeding.
Environmental Precautions:	Prevent liquid from entering public waterways.

Section 7 Handling and Storage

Safe Handling and Hygienic Practices:Reduce personal contact avoiding prolonged skin contact
with contaminated clothing. Wash after using.Storage Requirements:Keep in a tightly closed container away from open flame or other ignition
source. Adequate ventilation according to good engineering practices. Keep away from children.

Section 8 Exposure Controls

Engineering controls:	Adequate general ventilation. No special requirements under normal conditions.
Personal Protection:	
Ventilation:	Not required under normal conditions.
Respiratory:	No special requirements. Avoid breathing mists.
Eye Protection:	None required
Gloves:	Nitrile or Kevlar gloves recommended for a sensitive individual.
Ingestion:	Do not ingest
Exposure Limit Guidelines:	No established exposure guidelines

Section 9 Physical and Chemical Properties

Appearance and Odor:	A clear orange color. Citrus odor.	
Odor Threshold:	Unknown	
Physical State:	Liquid	
Viscosity:	1.7 cps. ASTM D-445	
Vapor Pressure:	<0.2 mm of Hg @ 20°C, <0.002 psi @ 68°F (Estimated)	
	Based on Thermogravimetric Analysis (TGA) Method.	
	Developed by vender.	
Volatile Percent:	100%	
Specific Gravity:	0.797, 6.65 lbs./US Gallon, ASTM D-4052	
Vapor Density:	(Air = 1), 4.5	
Evaporation Rate:	(Butyl Acetate = 1), 0.06, ASTM D-3539	
Boiling Point:	Initial – 186°C (367°F), ASTM D-1120	
Freezing Point:	This mixture of hydrocarbons has no true freezing point	
Pour Point:	-51°C (-60°F), ASTM D-1093-81	
pH of Concentrate:	Test not applicable	
Coefficient of Water/Oil Distribution: <0.1		
Solubility in Water:	<15 ppm. EPA modified Method 8015	
Kauri Butanol Number:	27 ASTM D-1133	
Dielectic Constant:	50,000 volts. ASTM D-877	

Section 10 Stability and Reactivity

Stability:	Stable
Conditions to Avoid:	Avoid the generation of mist and aspiration into the lungs
Incompatibility:	Avoid contact with strong oxidizing agents
Hazardous Decomposition:	Not expected under normal conditions
Hazardous Polymerization:	Does not occur

Section 11 Toxicity Information

LD50 of the Product:	Acute oral (Rat). >12,700 mg/Kg (16 ml/Kg)	
Teratogenicity and Embryotoxicity:	Unknown	
Mutagenicity:	Unknown	
Reproductive Toxicity:	Unknown	
Synergistic Materials:	Unknown	
Inhalation:	No toxic manifestations	
Draize Eye Irritation:	Score 0.00 (none)	
Primary Skin Irritation:	Irritation index, 0.2 (low)	
Muscle Tissue:	No deleterious effects	
Sensitizing Capability of the Product	t: Not expected in normal individuals	

ALL TEST DATA AVAILABLE ON REQUEST

Section 12 Environmental Tests

Aqueous Testing:Fundulus heteroclitus (Silverside fish): LC50, 4 days, 2000 ppm (low)Saprophytic Bacteria(Cold Temperature Strain):No minimum inhibiting product concentration.Product degraded extensively after 21 days. (Based on an analogous formulation).

Section 13 Disposal Considerations

RCRA Classification:	This product has been evaluated for RCRA characteristics and does not meet the criteria for a hazardous waste, if discarded in its purchased form.	
Volatile Organic Compound	(VOC) Content: Under the C_{12} Exemption, 31 Wt.%; Under Method 24, 794 g/Liter. (Values estimated). Contact local authority for appropriate compliance.	
Special Instructions:	The product is biodegradable based on activated sludge testing. Landfill or incinerate at authorized facilities.	

Section 14 Transportation Information

DOT Labeling:	Not required
Proper Shipping Name:	
Hazard Class:	
Identification Number:	

Section 15 Regulatory Information

OSHA and WHMIS Compliance: This MSDS prepared according to the 29 CFR 1910.1200 and ANSI Z400.1 Standards. These criteria meet the WHMIS Format Standard.

TSCA: Although components of this product find listing under the Toxic Substances Act (TSCA), this blended product requires no import or export declarations.

CERCLA, State and Local Planning (Reportable Quantities): Not required

SARA Title III Superfund: The product in its purchased form is not regulated under the SARA "Hazard Categories" under Sections 311 and 312 of the Superfund Amendment and the Reauthorization Act of 1986 (SARA Title III).

States Right-to-Know: Not required

Section 16 Other Information

Hazard Rating: Based on the NFPA 704 Standard. Health = 0, Flammability = 2, Reactivity = 0, Rating Scale: None = 0, Slight = 1, Moderate = 2, Severe = 3, Extreme = 4

Revision Date: 1 October 1998

The information expressed herein are those of the experts for Orange-Sol Industrial Products, Inc. We believe that the information contained herein is accurate and current as of the date of this Material Safety Data Sheet. Since the application in use of the information contained herein, and the conditions of use of the product are not under the control of Orange-Sol Industrial Products, Inc., the user must evaluate and determine whether the conditions for use and the application of the product, including proper disposal thereof, are appropriate, safe and legal.