

HYDRANAL™-Water Standard 0.1**34847-6X40ML**

Version 1.0

Revision Date 01/29/2018

Print Date 01/29/2018

SECTION 1. IDENTIFICATION

Product name : HYDRANAL™-Water Standard 0.1

Number : 000000022681

Product Use Description : Laboratory chemicals

Manufacturer or supplier's details : Manufactured by:
Honeywell International Inc.
1953 South Harvey Street
Muskegon, MI 49442
USA

Distributed by:
VWR International
2360 Argentia Road
Mississauga, Ontario L5N 5Z7
CANADA

For more information call : 1-800-932-5000
(Monday-Friday, 9:00am-5:00pm)

In case of emergency call : **Medical: 1-800-498-5701 or +1-303-389-1414**
: **Transportation (CHEMTREC): 1-800-424-9300 or**
: **+1-703-527-3887**
:
: (24 hours/day, 7 days/week)

SECTION 2. HAZARDS IDENTIFICATION**Emergency Overview**

Form : liquid

Color : colourless

Odor : aromatic

HYDRANAL™-Water Standard 0.1**34847-6X40ML**

Version 1.0

Revision Date 01/29/2018

Print Date 01/29/2018

Classification of the substance or mixture

Classification of the substance or mixture : Flammable liquids, Category 3
Acute toxicity, Category 4, Inhalation
Acute toxicity, Category 4, Dermal
Skin irritation, Category 2
Eye irritation, Category 2A
Specific target organ toxicity - single exposure, Category 3,
Respiratory system, Central nervous system
Aspiration hazard, Category 1

GHS Label elements, including precautionary statements

Symbol(s)



Signal word

: Danger

Hazard statements

: Flammable liquid and vapour.
May be fatal if swallowed and enters airways.
Harmful in contact with skin or if inhaled
Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation, and drowsiness or dizziness.

Precautionary statements

: **Prevention:**
Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ ventilating/ lighting/ equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
Wash skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

IF SWALLOWED: Immediately call a POISON CENTER/doctor.
IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
IF INHALED: Remove victim to fresh air and keep at rest in a

HYDRANAL™-Water Standard 0.1**34847-6X40ML**

Version 1.0

Revision Date 01/29/2018

Print Date 01/29/2018

position comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a POISON CENTER/doctor if you feel unwell.

Do NOT induce vomiting.

If skin irritation occurs: Get medical advice/ attention.

If eye irritation persists: Get medical advice/ attention.

Take off contaminated clothing and wash before reuse.

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage:

Store in a well-ventilated place. Keep container tightly closed.

Keep cool.

Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Mixture

Chemical name	CAS-No.	Concentration
o-Xylene	95-47-6	<100.00 %
Water	7732-18-5	0.01 %

SECTION 4. FIRST AID MEASURES

General advice : First aider needs to protect himself. Move out of dangerous area. Take off all contaminated clothing immediately.

HYDRANAL™-Water Standard 0.1**34847-6X40ML**

Version 1.0

Revision Date 01/29/2018

Print Date 01/29/2018

- | | |
|--------------|---|
| Inhalation | : Remove to fresh air. Keep patient warm and at rest. Call a physician. |
| Skin contact | : Wash off immediately with plenty of water. If skin irritation persists, call a physician. |
| Eye contact | : In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Protect unharmed eye. |
| Ingestion | : Never give anything by mouth to an unconscious person. Rinse mouth with water. Drink 1 or 2 glasses of water. Do NOT induce vomiting. Call a physician immediately. |

SECTION 5. FIREFIGHTING MEASURES

- | | |
|---|---|
| Suitable extinguishing media | : Foam
Carbon dioxide (CO2)
Dry powder |
| Unsuitable extinguishing media | : Do not use a solid water stream as it may scatter and spread fire. |
| Specific hazards during firefighting | : Flammable.
Vapours may form explosive mixtures with air.
Vapours are heavier than air and may spread along floors.
Vapors may travel to areas away from work site before igniting/flashing back to vapor source. |
| Special protective equipment for firefighters | : Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear. |
| Further information | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | |
|---|---|
| Personal precautions, protective equipment and emergency procedures | : Evacuate personnel to safe areas.
Wear personal protective equipment. Unprotected persons must be kept away.
Ensure adequate ventilation. |
|---|---|

HYDRANAL™-Water Standard 0.1**34847-6X40ML**

Version 1.0

Revision Date 01/29/2018

Print Date 01/29/2018

- Remove all sources of ignition.
- Environmental precautions : Should not be released into the environment.
Do not allow run-off from fire fighting to enter drains or water courses.
- Methods and materials for containment and cleaning up : Ventilate the area.
Do not use sparking tools.
Use explosion-proof equipment.
Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE**Handling**

- Precautions for safe handling : Wear personal protective equipment.
Use only in well-ventilated areas.
- Advice on protection against fire and explosion : Keep product and empty container away from heat and sources of ignition.
No smoking.
Take precautionary measures against static discharges.
Vapours may form explosive mixtures with air.

Storage

- Conditions for safe storage, including any incompatibilities : Store in original container.
Keep containers tightly closed in a dry, cool and well-ventilated place.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- Protective measures : Ensure that eyewash stations and safety showers are close to the workstation location.
Legal requirements are to be considered in regard of the selection, use and care of personal protective equipment.
Do not breathe vapours or spray mist.
- Engineering measures : Use with local exhaust ventilation.
Prevent vapour buildup by providing adequate ventilation during

HYDRANAL™-Water Standard 0.1

34847-6X40ML

Version 1.0

Revision Date 01/29/2018

Print Date 01/29/2018

and after use.

Eye protection : Safety goggles

Hand protection : Protective gloves
Gloves must be inspected prior to use.
Replace when worn.

Skin and body protection : Protective suit

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hygiene measures : Take off all contaminated clothing immediately.
Recommended preventive skin protection
When using do not eat or drink.
Wash hands before breaks and at the end of workday.
Avoid contact with the skin and the eyes.

Exposure Guidelines

Components	CAS-No.	Value	Control parameters	Update	Basis
o-Xylene	95-47-6	TWA : Time weighted average	434 mg/m ³ (100 ppm)	07 2009	CAD AB OEL:Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

o-Xylene	95-47-6	STEL : Short term exposure limit	651 mg/m ³ (150 ppm)	07 2009	CAD AB OEL:Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)
----------	---------	-------------------------------------	------------------------------------	------------	---

SAFETY DATA SHEET



HYDRANAL™-Water Standard 0.1

34847-6X40ML

Version 1.0

Revision Date 01/29/2018

Print Date 01/29/2018

o-Xylene	95-47-6	STEL : Short term exposure limit	(150 ppm)	07 2007	CAD BC OEL:Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)
o-Xylene	95-47-6	TWA : Time weighted average	(100 ppm)	07 2007	CAD BC OEL:Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)
o-Xylene	95-47-6	TWA : Time weighted average	(100 ppm)	03 2014	CAD MB OEL:Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)
o-Xylene	95-47-6	STEL : Short term exposure limit	(150 ppm)	03 2014	CAD MB OEL:Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

SAFETY DATA SHEET



HYDRANAL™-Water Standard 0.1

34847-6X40ML

Version 1.0

Revision Date 01/29/2018

Print Date 01/29/2018

o-Xylene	95-47-6	STEL : Short Term Exposure Limit (STEL):	(150 ppm)	11 2010	CAD ON OEL:Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)
o-Xylene	95-47-6	TWA : Time weighted average	(100 ppm)	11 2010	CAD ON OEL:Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)
o-Xylene	95-47-6	8 HR ACL : 8 hour average contamin ation limit:	(100 ppm)	05 2009	CAD SK OEL:Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)
o-Xylene	95-47-6	15 MIN ACL : 15 minute average contamin ation limit:	(150 ppm)	05 2009	CAD SK OEL:Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)
o-Xylene	95-47-6	STEL : Short term exposure limit	651 mg/m3 (150 ppm)	12 2008	OEL (QUE):Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

HYDRANAL™-Water Standard 0.1**34847-6X40ML**

Version 1.0

Revision Date 01/29/2018

Print Date 01/29/2018

o-Xylene	95-47-6	TWA : Time weighted average	434 mg/m3 (100 ppm)	12 2008	OEL (QUE):Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)
----------	---------	--------------------------------------	------------------------	------------	---

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: liquid
Color	: colourless
Odor	: aromatic
pH	: Note: no data available
Melting point/range	: -25 °C
Boiling point/boiling range	: 143 - 145 °C at 1,013 hPa
Flash point	: ca. 86 °F (30 °C)
Evaporation rate	: Note: no data available
Lower explosion limit	: 1.7 %(V)
Upper explosion limit	: 7.6 %(V)
Vapor pressure	: 0.67 hPa at 20 °C(68 °F)
Density	: 0.88 g/cm3 at 20 °C

HYDRANAL™-Water Standard 0.1**34847-6X40ML**

Version 1.0

Revision Date 01/29/2018

Print Date 01/29/2018

Water solubility : Note: insoluble

Partition coefficient:
n-octanol/water : log Pow: 3.13 at 25 °C

Ignition temperature : 465 °C

Decomposition temperature : Note: At normal pressure may be distilled without decomposition.

Viscosity, kinematic : Note: no data available

SECTION 10. STABILITY AND REACTIVITY

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Hazardous polymerization does not occur.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong oxidizing agents
Formation of explosive gas/air mixtures.

Hazardous decomposition products : In case of fire hazardous decomposition products may be produced such as:
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11. TOXICOLOGICAL INFORMATION

Acute oral toxicity : LD50: 3,523 mg/kg
Species: Rat, male
Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)

Acute inhalation toxicity : Note: Classification based on Annex VI of regulation 1272/2008/EC.

HYDRANAL™-Water Standard 0.1**34847-6X40ML**

Version 1.0

Revision Date 01/29/2018

Print Date 01/29/2018

Acute dermal toxicity	: Note: Classification based on Annex VI of regulation 1272/2008/EC.
Skin irritation	: Result: Irritating to skin.
Eye irritation	: Result: Irritating to eyes.
Sensitisation	: Note: Not classified due to data which are conclusive although insufficient for classification.
Genotoxicity in vitro	: Note: Not classified due to data which are conclusive although insufficient for classification.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity effects**

Toxicity to fish o-Xylene	: LC50: 16.9 mg/l Exposure time: 96 h Species: Carassius auratus (goldfish)
Toxicity to algae	: Growth rate EC50: 2.2 mg/l Exposure time: 72 h Species: Pseudokirchneriella subcapitata (green algae) Method: OECD Test Guideline 201

Further information on ecology

Additional ecological information	: Should not be released into the environment.
-----------------------------------	--

SECTION 13. DISPOSAL CONSIDERATIONS

HYDRANAL™-Water Standard 0.1**34847-6X40ML**

Version 1.0

Revision Date 01/29/2018

Print Date 01/29/2018

Disposal methods : Observe all Federal, State, and Local Environmental regulations.

SECTION 14. TRANSPORT INFORMATION

TDG UN/ID No. : UN 1307
Proper shipping name : XYLENES
Class : 3
Packing group : III
Hazard Labels : 3

IATA UN/ID No. : UN 1307
Description of the goods : XYLENES
Class : 3
Packaging group : III
Hazard Labels : 3
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355
Packing instruction (passenger aircraft) : Y344

IMDG UN/ID No. : UN 1307
Description of the goods : XYLENES
Class : 3
Packaging group : III
Hazard Labels : 3
EmS Number : F-E, S-D
Marine pollutant : no

SECTION 15. REGULATORY INFORMATION**Inventories**

US. Toxic Substances : On TSCA Inventory
Control Act

Australia. Industrial : On the inventory, or in compliance with the inventory
Chemical (Notification and
Assessment) Act

Canada. Canadian : All components of this product are on the Canadian DSL

HYDRANAL™-Water Standard 0.1**34847-6X40ML**

Version 1.0

Revision Date 01/29/2018

Print Date 01/29/2018

Environmental Protection
Act (CEPA). Domestic
Substances List (DSL)

Japan. Kashin-Hou Law List : On the inventory, or in compliance with the inventory

Korea. Existing Chemicals
Inventory (KECI) : On the inventory, or in compliance with the inventory

Philippines. The Toxic
Substances and Hazardous
and Nuclear Waste Control
Act : On the inventory, or in compliance with the inventory

China. Inventory of Existing
Chemical Substances : On the inventory, or in compliance with the inventory

New Zealand. Inventory of
Chemicals (NZIoC), as
published by ERMA New
Zealand : On the inventory, or in compliance with the inventory

National regulatory information**WHMIS**

Components : o-Xylene 95-47-6

NPRI

Components : o-Xylene 95-47-6

SECTION 16. OTHER INFORMATION

	HMIS III	NFPA
Health hazard	: 2*	2
Flammability	: 3	3
Physical Hazard	: 0	
Instability	:	0

* - Chronic health hazard

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

HYDRANAL™-Water Standard 0.1**34847-6X40ML**

Version 1.0

Revision Date 01/29/2018

Print Date 01/29/2018

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Prepared by Honeywell Performance Materials and Technologies Product Stewardship Group