

SpillTech 5440 McGinnis Village Place Suite 102 Alpharetta, GA 30005 Phone: 1-800-228-3877 Fax: 1-800-872-3764 www.spilltech.com

MATERIAL SAFETY DATA SHEET

SECTION I: IDENTIFICATION OF PRODUCT

PRODUCT NAME:Gray Universal Fine Fiber SorbentsCHEMICAL FAMILY:OlefinMANUFACTURER'S NAME:SpillTech

Manufacturing Location:

SpillTech Brookley Industrial Complex 1627 O'Donoghue Street Mobile, AL 36615

Customer Service Telephone Number: 1-800-228-3877 Technical Information Telephone Number: 1-251-694-0102 ext.121 Date Prepared: April 29, 2002

SECTION II: HAZARDOUS INGREDIENTS

INGREDIENTS	PERCENT	CAS NUMBER	<u>OSHA PEL</u>	ACGIH TLV
Polypropylene	98.3%	9003-07-0	N/A	N/A
Surfactant	1.4%	N/A	N/A	N/A
Gray Pigment	0.3%	N/A	N/A	N/A
(Carbon Black)	23.5%	1333-86-4	3.5mg/m ³	3.5mg/m ³
(Polypropylene)	76.5%	9003-07-0	N/A	N/A

Note: Sub-ingredients of main ingredient are in parentheses

SECTION III: HAZARDS IDENTIFICATION

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) RATING:

HEALTH:	0
FLAMMABILITY:	1
REACTIVITY:	0

*Not considered a hazardous material at temperatures below melting point. Not considered a controlled substance or a carcinogen.

SECTION IV: FIRST AID MEASURES

EYE CONTACT:Use eyewash, consult physician if accompanied by pain or irritation.SKIN CONTACT:N/AINHALATION:N/AINGESTION:N/A

SECTION V: FIRE FIGHTING MEASURES

FLASH POINT: AUTO IGNITION: FLAMMABLE LIMITS: FIRE EXTINGUISHING MEDIA: SPECIAL FIRE FIGHTING PROCEDURES: UNUSUAL FIRE AND EXPLOSION HAZARDS:	 329° C (625° F) 357° C (675° F) N/A Water, Foam, CO2, Dry Chemical Standard procedures for Class A fires Some carbon monoxide formation is possible under oxygen-lean conditions. Matting will not support combustion. Sorbents will take on the characteristics/properties of whatever liquid is absorbed. Therefore, all measures must be taken as if you were handling the liquid itself. Sorbents do not make the liquid less hazardous. Always

SECTION VI: ACCIDENTAL RELEASE MEASURES

No special steps to be taken if material is spilled or released.

SECTION VII: HANDLING AND STORAGE

Store in dry area. Do not store near open flame, high heat, strong oxidants, or halogenated hydrocarbons. Polypropylene, when heated, becomes very sticky and will burn. Use self-contained air masks to enter smoky area in the event of fire. Adequate ventilation is required to remove decomposition products when temperature exceeds melting point. Avoid contact with melted product.

Sorbents will take on the characteristics/properties of whatever liquid is absorbed. Therefore, all measures must be taken as if you were handling the liquid itself. Sorbents do not make the liquid less hazardous. Always refer to the MSDS for the chemical absorbed before proceeding

SECTION VIII: EXPOSURE CONTROLS/ PERSONAL PROTECTION EQUIPMENT

RESPIRATORY PROTECTION: VENTILATION: PROTECTIVE GLOVES: EYE PROTECTION: None Required None Required None Required Safety glasses with side shields are recommended as a good practice for industrial safety. None Required

OTHER PROTECTIVE EQUIPMENT (SPECIFY):

SECTION IX: PHYSICAL DATA

APPEARANCE AND ODOR:	Gray & virtually odor free
SPECIFIC GRAVITY:	0.88 - 0.92
BOILING POINT (C):	Not Applicable
MELTING POINT (C):	>160° C (320° F)
SOLUBILITY IN WATER:	Insoluble
PERCENT VOLATILE BY VOLUME:	N/A
EVAPORATION RATE:	N/A
VAPOR PRESSURE (mm Hg):	N/A
VAPOR DENSITY (Air = 1):	N/A

SECTION X: TRANSPORT INFORMATION

DOT CLASSIFICATION: Non Hazardous

SECTION XI: WASTE XI DISPOSAL METHOD

Disposal must be done in accordance with local, state and federal regulations based on chemicals adsorbed by products.

Sorbents will take on the characteristics/properties of whatever liquid is absorbed. Therefore, all measures must be taken as if you were handling the liquid itself. Sorbents do not make the liquid less hazardous. Always refer to the MSDS for the chemical absorbed before proceeding

SECTION XII: PREPARATION

The information contained herein is given in good faith, but no warranty, expressed or implied, is made.

DATE ISSUED: April 29, 2002 UPDATED: February 2005 PREPARED BY: SpillTech, Telephone Number: 1-800-228-3877.