

Standard Laboratory Use Sterilizer

SN200C/210C/300C/310C/500C/510C

Operating
temp. range

45°C to 135°C

Max. operating
pressure

0.255MPa

Internal capacity

20L (SN200C/210C) / 32L (SN300C/310C) / 47L (SN500C/510C)

High-performance, easy operation and ergonomically designed sterilizer featuring easy top loading and handling of samples



- Maximum sterilizing temperature goes up to 135°C suitable for protein modification
- By simple setting and operation, these sterilizers manage ordinary sterilization, sterilization of culture mediums and liquids, and melting of culture mediums
- Custom programs can be saved for repeated use
- Standard equipped with timer start and pre-heating features for efficient use of time and cooling fan to shorten cool down time
- Mobile on wheels


Enhanced safety device

- Lid interlock mechanism
- Drain bottle unset alarm
- Memory malfunction
- Automatic shutdown when malfunction
- Self-diagnostic functions

Specifications

Model	SN200C	SN210C	SN300C	SN310C	SN500C	SN510C
System	Automatic high-pressure steam sterilization					
Operating temperature range	45~135°C					
Max. working pressure	0.255MPa					
Ambient temperature	5~35°C					
Lid	Manual upward opening with an interlock for safety					
Heater	100V, 600W x 2 units		100V, 800W x 2 units		100V, 950W x 2 units	
Exhaust valve	One exhaust valve and one slow release valve					
Connection ports for optional accessories	Total 3 ports. Female thread for sample temp. sensor (1/4"), Female thread for chamber temp. sensor (1/4"), Female thread pressure sensor (branching from the solenoid valve tubing)					
Cooling fan	Axial fan motor					
Temp. controller	PID control by microprocessor					
Temp. display / setting	Digital display / digital setting by ▲/▼ keys					
Timer / Timer resolution	0 or 1 min. to 99 hrs 59 min. / 1 min.					
Operation mode	Instrument sterilization course, liquid sterilization course, sterilization and keep warm course, melting and keep warm course, customer-programmed course					
Other function	Key locking, presetting, saving, preheating, forced cooling, sample temperature sensor (option), pattern locking, up to 20 error log saving, display of accumulated working time / present time, ON-OFF beeping setting					
Safety device	Sensor failure detection, SSR short-circuit, broken heater wire, prevention of idle heating (liquid expansion type), alarm against the absence of a drain bottle, failure in locking the lid, memory error detection, pressure relief valve (0.255 MPa)					
External dimensions (WxDxHmm)	400 x 530 x 848		460 x 590 x 848		460 x 590 x 1068	
Internal dimensions of chamber	I.D.240 x D445 mm		I.D.300 x D445 mm		I.,D.300 x D665 mm	
Internal capacity	20L		32L		47L	
Weight	~65kg		~75kg		~85kg	
Power source	AC100~120V(12.5~15A)	AC200~240V(6.5~7.5A)	AC100~120V(12.5~15A)	AC200~240V(8.5~10A)	AC100~120V(19.5~23.5A)	AC200~240V(10~12A)
Accessories	2 pcs. stainless steel mesh basket (Dia.205 x D204mm), OSM-60		2 pcs. stainless steel mesh basket (Dia.262 x D204mm), OSM-70		3 pcs. stainless steel mesh basket (Dia.262 x D204mm), OSM-70	
	Vapor cup x 1, Drain bottle x 1, Drain board x 1, Chemical indicator 1 set (30 pieces), Filter x 1					

Control panel



Choose a sterilization program

Sterilize/Normal Course	Sterilization of equipment such as flask, beaker, test tube, scissors
Sterilize/Liquid Course	Sterilization of culture and re-agents and keep warm
Sterilize Warm Course	Dissolve and keep warm of the agar medium
Melt Warm Course	Sterilization of liquid, purified water and dilution water
Manual Course	Customized temperature and time settings

Standard Equipped with Cooling Fan & Slow Release Valve

- For decompression and prevention of liquid samples from bumping
- Cooling fan cool to a safe temperature after sterilization completes
- Shortens time before samples are taken out
- Natural cooling by OFF setting

Features

Support GLP / GMP Inspection



Standard equipped with 2 sensor ports on the main unit




Optional recorder and high performance pressure gauge

Easy to drain out sterilizing water



Easier maintenance with larger diameter drain pipe

Sterilization starts automatically by sample temperature sensor



With the optional mounted sample temperature sensor, desired sample temperature can be precisely maintained to ensure thorough sterilization

Front Loading Drain Bottle



The drain bottle is located in front for easy access and drain water level can be monitored without opening the cabinet door

Optional items

Baskets with adjustable stainless steel perforated plate

Mesh baskets

Stainless solid baskets

Baskets with stacking fittings

Stainless baskets

Stainless buckets



Product code	Model	Description	Corresponding models
241087	OSM-60	Mesh basket	SN200C/210C
241088	OSM-70		SN300C/310C/500C/510C
241089	OSM-80		SN500C/510C
241093	OSQ-30	Mesh basket with stacking fittings	SN200C/210C, with two fittings
241092	OSQ-40		SN300C/310C, with two fittings
241091	OSQ-50		SN500C/510C, with three fittings
241096	OSQ-60	Mesh basket with adjustable stainless steel perforated plate	SN200C/210C, with 1 plate
241095	OSQ-70		SN300C/310C, with 1 plate
241094	OSQ-80		SN500C/510C, with 2 plates
241083	OSR-10	Stainless solid basket	SN200C/210C
241084	OSR-20		SN300C/310/500C/510C
241150	OSN10	Stainless bucket	SN200C/210C
241151	OSN12		SN300C/310/500C/510C
241153	OSR-70*	Chamber temp. sensor	Type T thermocouple, 3 pcs./set
241154	OSN16 *	Sample temp. sensor	Type T thermocouple, 1 pc.
241155	OSN18 *	Pressure gauge	External installation
241157	OSN20 *	External alarm output terminal	
241158	OSN22 *	Temp. output terminal	4 - 20 mA
241159	OSN24 *	Time-up output terminal	Relay, contact output

* Please specify when ordering main unit.