

## Material Safety Data Sheet

United States  
English

## Section 1. Chemical product and company identification

Product name **HiTrap™ Chelating HP 1 ml, 5 x 1 ml**

Catalogue Number **17-0408-01**



**Material uses** Industrial applications: Analytical chemistry. Research. Liquid chromatography.  
**Product type** Liquid.  
**Validation date** 17 September 2013  
**Print date** 17 September 2013  
**Supplier** GE Healthcare UK Ltd  
Amersham Place  
Little Chalfont  
Buckinghamshire HP7 9NA  
England  
+44 0870 606 1921

**In case of emergency**

US	ChemTrec (US)	1-800-424-9300
Canada	ChemTrec (US)	1-703-527-3887

## 2. Hazards identification

**Physical state** Liquid. [and Suspension.]

**Color** Solution : Colorless. / Suspension. : White. White to yellowish.

**Odor** Sweetish. Alcohol-like. [Slight]

**Signal word** **WARNING!**

**Hazard statements** **FLAMMABLE LIQUID AND VAPOR. COMBUSTIBLE. CAUSES EYE IRRITATION. MAY CAUSE RESPIRATORY TRACT AND SKIN IRRITATION. CONTAINS MATERIAL THAT CAN CAUSE TARGET ORGAN DAMAGE. CANCER HAZARD - CONTAINS MATERIAL WHICH CAN CAUSE CANCER.**

**Precautionary measures** Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Do not breathe vapor or mist. Use only with adequate ventilation. Do not eat, drink or smoke when using this product. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Keep container tightly closed. Use personal protective equipment as required. Wash thoroughly after handling.

**OSHA/HCS status** This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

**Routes of entry** Dermal contact. Eye contact. Inhalation. Ingestion.

**Potential acute health effects**

<b>Eyes</b>	Irritating to eyes.
<b>Skin</b>	Moderately irritating to the skin.
<b>Inhalation</b>	Moderately irritating to the respiratory system.
<b>Ingestion</b>	No known significant effects or critical hazards.

**Potential chronic health effects**

<b>Chronic effects</b>	Contains material that can cause target organ damage.
<b>Carcinogenicity</b>	Contains material which can cause cancer. Risk of cancer depends on duration and level of exposure.
<b>Mutagenicity</b>	No known significant effects or critical hazards.
<b>Teratogenicity</b>	No known significant effects or critical hazards.
<b>Developmental effects</b>	No known significant effects or critical hazards.
<b>Fertility effects</b>	No known significant effects or critical hazards.
<b>Target organs</b>	Contains material which causes damage to the following organs: kidneys. Contains material which may cause damage to the following organs: blood, the reproductive system, liver, upper respiratory tract, skin, eyes, central nervous system (CNS).

**Inhalation** Adverse symptoms may include the following:  
respiratory tract irritation  
coughing



Article Number

17040801



Page: 1/7

Validation date 17 September 2013

Version 5.1

<b>Ingestion</b>	No specific data.
<b>Skin</b>	Adverse symptoms may include the following: irritation redness
<b>Eyes</b>	Adverse symptoms may include the following: pain or irritation watering redness
<b>Medical conditions aggravated by over-exposure</b>	Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.
See toxicological information (Section 11)	

### 3. Composition/information on ingredients

Name	CAS number	% by weight
ethanol	64-17-5	14 - 19

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

### Section 4. First aid measures

<b>Eye contact</b>	Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.
<b>Skin contact</b>	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.
<b>Inhalation</b>	Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.
<b>Ingestion</b>	Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.
<b>Protection of first-aiders</b>	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### Section 5. Fire-fighting measures

<b>Flammability of the product</b>	Flammable liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.
<b>Extinguishing media</b>	
<b>Suitable</b>	Use dry chemical, CO <sub>2</sub> , water spray (fog) or foam.
<b>Not suitable</b>	Do not use water jet.
<b>Special exposure hazards</b>	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
<b>Hazardous combustion products</b>	Decomposition products may include the following materials: carbon dioxide carbon monoxide
<b>Special protective equipment for fire-fighters</b>	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

<b>Personal precautions</b>	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flames, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
<b>Environmental precautions</b>	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
<b>Methods for cleaning up</b>	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.
<b>Small spill</b>	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.



## Section 7. Handling and storage

### Handling

Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Avoid exposure - obtain special instructions before use. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

### Storage

Store between the following temperatures: 4 to 30°C (39.2 to 86°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

### Ingredient

ethanol

### Exposure limits

**ACGIH TLV (United States, 3/2012). Notes: 1996 Adoption Refers to Appendix A -- Carcinogens.**

STEL: 1000 ppm 15 minutes.

**NIOSH REL (United States, 6/2009). Notes:**

TWA: 1900 mg/m<sup>3</sup> 10 hours.

**NIOSH REL (United States, 6/2009).**

TWA: 1000 ppm 10 hours.

**OSHA PEL (United States, 6/2010).**

TWA: 1900 mg/m<sup>3</sup> 8 hours.

TWA: 1000 ppm 8 hours.

**OSHA PEL 1989 (United States, 3/1989).**

TWA: 1900 mg/m<sup>3</sup> 8 hours.

TWA: 1000 ppm 8 hours.

### Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### Engineering measures

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

### Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

### Personal protection

#### Respiratory

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: A respirator is not needed under normal and intended conditions of product use.

#### Hands

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. 1 - 4 hours (breakthrough time): butyl rubber, neoprene

#### Eyes

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. Recommended: safety glasses with side-shields


#### Skin

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Recommended: lab coat



**Environmental exposure controls** Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

**Personal protective equipment (Pictograms)**



## Section 9. Physical and chemical properties

<b>Physical state</b>	Liquid. [and Suspension.]
<b>Flash point</b>	Closed cup: 38 to 43°C (100.4 to 109.4°F)
<b>Color</b>	✓ Solution : Colorless. / Suspension. : White. White to yellowish.
<b>Odor</b>	Sweetish. Alcohol-like. [Slight]
<b>Taste</b>	Alcohol-like.
<b>Volatility</b>	14 to 19% (w/w)
<b>Odor threshold</b>	180 ppm
<b>Ionicity (in water)</b>	Non-ionic.
<b>Solubility</b>	Easily soluble in the following materials: cold water and hot water.

## Section 10. Stability and reactivity

<b>Chemical stability</b>	✓ The product is stable.
<b>Conditions to avoid</b>	Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
<b>Incompatible materials</b>	✓ Reactive or incompatible with the following materials: oxidizing materials
<b>Possibility of hazardous reactions</b>	✓ Under normal conditions of storage and use, hazardous reactions will not occur.

## Section 11. Toxicological information

### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
✓ Ethanol	LC50 Inhalation Vapor	Rat	124700 mg/m <sup>3</sup>	4 hours

**Conclusion/Summary** Not available.

### Chronic toxicity

**Conclusion/Summary** Not available.

### Irritation/Corrosion

**Conclusion/Summary**

**Skin** ✓ Repeated exposure may cause skin dryness or cracking.

### Sensitizer

**Conclusion/Summary** Not available.

### Carcinogenicity

**Conclusion/Summary** Not available.

### Classification

Product/ingredient name	OSHA	IARC	NTP	ACGIH	EPA	NIOSH
✓ Ethanol	-	1	-	A3	-	-

### Mutagenicity

**Conclusion/Summary** Not available.

### Teratogenicity

**Conclusion/Summary** Not available.

### Reproductive toxicity


**Conclusion/Summary** Not available.



## Section 12. Ecological information

**Environmental effects** No known significant effects or critical hazards.

### Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
 Ethanol	Acute EC50 17.921 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 2000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 25500 µg/l Marine water	Crustaceans - Artemia franchiscana - Larvae	48 hours
	Acute LC50 42000 µg/l Fresh water	Fish - Oncorhynchus mykiss	4 days
	Chronic NOEC 4.995 mg/l Marine water	Algae - Ulva pertusa	96 hours

### Conclusion/Summary

Not available.

### Persistence/degradability

Product/ingredient name	Test	Result	Dose	Inoculum
 Ethanol	-	100 % - Readily - 20 days	-	-


### Conclusion/Summary

Not available.

**Toxicity of the products of biodegradation** The product itself and its products of degradation are not toxic.

**Other adverse effects** No known significant effects or critical hazards.

## Section 13. Disposal considerations

**Waste disposal**  The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

**Waste stream** Code: D001  
Classification: Ignitability

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.



## Section 14. Transport information


IATA-DGR Class Classes PG\*


PG\* : Packing group


## Section 15. Regulatory information


**HCS Classification**  Combustible liquid  
Irritating material  
Carcinogen  
Target organ effects


**U.S. Federal regulations**  **SCA 8(a) CDR Exempt/Partial exemption:** Not determined  
 **United States inventory (TSCA 8b):** All components are listed or exempted.

**Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)**  Not listed

**Clean Air Act Section 602 Class I Substances**  Not listed

**Clean Air Act Section 602 Class II Substances**  Not listed

**DEA List I Chemicals (Precursor Chemicals)**  Not listed

**DEA List II Chemicals (Essential Chemicals)**  Not listed

### SARA 302/304

#### Composition/information on ingredients



Article Number

17040801



Page: 5/7

Validation date 17 September 2013

Version 5.1

No products were found.

**SARA 304 RQ**

Not applicable.

**SARA 311/312****Classification**

Fire hazard  
 Immediate (acute) health hazard  
 Delayed (chronic) health hazard

**Composition/information on ingredients**

Name	%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
Ethanol	14 - 19	Yes.	No.	No.	Yes.	Yes.

**State regulations****Massachusetts**

The following components are listed: ETHYL ALCOHOL

**New York**

None of the components are listed.

**New Jersey**

The following components are listed: ETHYL ALCOHOL; ALCOHOL

**Pennsylvania**

The following components are listed: DENATURED ALCOHOL

**California Prop. 65****WARNING:** This product contains a chemical known to the State of California to cause cancer.

Ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
Ethanol	Yes.	No.	No.	No.

**United States inventory (TSCA 8b)**

All components are listed or exempted.

**International regulations****International lists**

**Australia inventory (AICS):** All components are listed or exempted.  
**China inventory (IECSC):** All components are listed or exempted.  
**Japan inventory:** Not determined.  
**Korea inventory:** All components are listed or exempted.  
**Malaysia Inventory (EHS Register):** Not determined.  
**New Zealand Inventory of Chemicals (NZIoC):** All components are listed or exempted.  
**Philippines inventory (PICCS):** All components are listed or exempted.  
**Taiwan inventory (CSNN):** Not determined.

**Chemical Weapons Convention  
List Schedule I Chemicals**

Not listed

**Chemical Weapons Convention  
List Schedule II Chemicals**


Not listed

**Chemical Weapons Convention  
List Schedule III Chemicals**

Not listed

**Section 16. Other information****Label requirements**

FLAMMABLE LIQUID AND VAPOR. COMBUSTIBLE. CAUSES EYE IRRITATION. MAY CAUSE RESPIRATORY TRACT AND SKIN IRRITATION. CONTAINS MATERIAL THAT CAN CAUSE TARGET ORGAN DAMAGE. CANCER HAZARD - CONTAINS MATERIAL WHICH CAN CAUSE CANCER.

**The customer is responsible for determining the PPE code for this material.****National Fire Protection  
Association (U.S.A.)**

Indicates information that has changed from previously issued version.

**History**

Date of printing	17 September 2013	Date of previous issue	23 November 2007
Date of issue	17 September 2013	Version	5.1

**Notice to reader**

Article Number

17040801



9 5 1 7 0 4 0 8 0 1

Page: 6/7

Validation date 17 September 2013

Version 5.1

---

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

---

---

