Description: White Diamond Series Undercounter Refrigerator Built-In-LEFT HINGED 4.6 Cu. Ft. Capacity One solid swing door, left hinged Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts 2 probes; 1 in air and 1 in glycol bottle Adjustable operating temperature range: 1°C – 10°C	Product Name:	PR051WWWADALH/0 VWR #76271-356
HINGED 4.6 Cu. Ft. Capacity One solid swing door, left hinged Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts 2 probes; 1 in air and 1 in glycol bottle Adjustable operating temperature range: 1°C – 10°C		
Three shelves (two adjustable/one fixed) with guard rail on back to prevent product from pushing against back wall Back wall evaporator cover Forced draft circulation Keyed door lock Magnetic door gasket for positive seal Heavy duty door handle Leveling legs LED interior light Probe access port (3/8") Powder coat exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R600a), foam insulation and packaging Three year parts and labor warranty Pyxis®, Omnicell® and AcuDose RX® compatible Exterior dimensions: 23 ¾"W x 25 ½"D x 31 15/16"H Cycle defrost 115V, 60 Hz, 1.74 Amps, 1/8 HP ADA compliant UL/C-UL listed		White Diamond Series Undercounter Refrigerator Built-In-LEFT HINGED 4.6 Cu. Ft. Capacity One solid swing door, left hinged Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts 2 probes; 1 in air and 1 in glycol bottle Adjustable operating temperature range: 1°C – 10°C Three shelves (two adjustable/one fixed) with guard rail on back to prevent product from pushing against back wall Back wall evaporator cover Forced draft circulation Keyed door lock Magnetic door gasket for positive seal Heavy duty door handle Leveling legs LED interior light Probe access port (3/8") Powder coat exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R600a), foam insulation and packaging Three year parts and labor warranty Pyxis®, Omnicell® and AcuDose RX® compatible Exterior dimensions: 23 ¾"W x 25 ½"D x 31 15/16"H Cycle defrost 115V, 60 Hz, 1.74 Amps, 1/8 HP ADA compliant